


Vibrator


LV 20 and LV 20 F

EN-US



LIEBHERR





LV 20

With the LV 20 Liebherr offers a powerful and innovative high-frequency vibrator for the installation or extraction of steel sheet piles, steel pipes or other piling elements. Through the use of state-of-the-art components the vibrator is particularly easy to maintain. It is leader mounted on the carrier machines of the LRB series. The rope crowd systems of these machines provide the necessary push and pull forces.

Key Features

- Eccentric moment : 0–20 kgm / 0–145 ft lb
- Max. centrifugal force: 1160 kN / 260,778 lbf
- Max. frequency : 2500 rpm
- Dynamic weight including clamp: 2900 kg / 6,395 lbs
- Total weight including clamp: 4400 kg / 9,700 lbs

Application

- Sheet piling

Symmetrical suspension and new linear guide

more efficiency, higher endurance, less maintenance

Cooling system


preheating of gearbox, more efficient cooling and lubrication

Amplitude adjustment

maintenance-free, robust, with continuous control

Large dimensioned main bearings

longer service life



LV 20 F

The high-frequency vibrator LV 20 F is specially designed for all common methods of soil improvement. This includes the installation of vibro-replacement columns or concrete vibration columns. The flexible suspension of the exciter block in the yoke counterbalances the angular errors between the piling element and the leader, which is unavoidable in this application. This also minimises the loss of performance as well as the wear on all parts.

Key Features

- Eccentric moment : 0–20 kgm / 0–145 ft lb
- Max. centrifugal force: 1160 kN / 260,778 lbf
- Max. frequency : 2500 rpm
- Dynamic weight including clamp: 3200 kg / 7,055 lbs
- Total weight including clamp: 4700 kg / 10,362 lbs

Application

- Soil improvement

No linear guide

Means no wear on the vibrator and piling element

Additional cooling system

for continuous operation of the vibrator

Amplitude adjustment

maintenance-free, robust, with continuous control


Large dimensioned main bearings

longer service life

Transport frame

LV 20

LV 20 F



Weights	LV 20	LV 20 F
Vibrator	7,959 lbs / ca. 3610 kg	8,400 lbs / ca. 3810 kg
Clamp	1,874 lbs / ca. 850 kg	1,874 lbs / ca. 850 kg
Feeder aid	66 lbs / ca. 30 kg	66 lbs / ca. 30 kg
Transport frame	2,778 lbs / ca. 1260 kg	2,403 lbs / ca. 1090 kg
Total weight	12,677 lbs / ca. 5750 kg	12,743 lbs / ca. 5780 kg