


Optimal accessibility in the Port of Rostock


- No shipping obstacles, locks, bridges etc.
- For ships with a draught of 13 metres, length of 300 metres and a width of 45 metres (special permissions possible)
- Connection to the hinterland via German rail network and to the A19 and A20 motorways

Suitable for several heavy loads


- Wind & offshore industry
- Shipbuilding industry
- Plant construction
- And many more







Potential operating area of the TCC 78000




Working radius of the TCC 78000

Customer benefits

- Heavy duty crane with 1,600 mt lifting capacity
- Optimal flexibility along the gantry track
- Efficient transloading operations in one work step
- Ideal hinterland connection via road and rail
- Storage area available on Liebherr yard
- High permissible ground bearing capacities on adjacent storage areas

Specifications TCC 78000

Drive system	Electro hydraulic
Slewing range	360°
Operating range	420 m gantry track (designed to travel under full load)
Maximum lifting capacities (SWL)	
Main Hoist 1	1,600 mt at 36 m radius
Aux. Hoist 1	500 mt at 62 m radius
Aux. Hoist 2	25 mt at 106 m radius
Maximum lifting heights	
Main Hoist 1	118 m
Aux. Hoist 1	134 m
Aux. Hoist 2	158 m



Get in contact

Visit our website for more information and request an individual offer for your heavy lift project.

