

# LIEBHERR

# Contents

<b>1</b> 1.1	Appliance at a glance Scope of delivery	<b>3</b> 3
1.2 1.3	Overview of the appliance and equipment SmartDevice	3 3
1.4	Appliance range of use	4
1.5 1.6	Conformity SVHC substances according to REACH regulation.	4
1.7 1.8	EPREL database Spare parts	4 4
2	General safety instructions	4
3	Functionality of the Touch & Swipe display	6
3.1	Navigation and symbol explanation	6
3.2 3.3	Menus Sleep mode	6 7
4	Putting into operation	7
4.1	Switching on appliance (first use)	7
<b>5</b> 5.1	Storage Information regarding storage	7 7
5.2	Storage sketch	7
6	Saving energy	8
7	Controls	8
7.1 7.1.1	Control and display elements Status display	8 8
7.1.2	Display symbols	9
7.1.3 7.2	Acoustic signals Appliance functions	9 9
7.2.1	Notes on the appliance functions	9
7.2.2 7.2.3	Switching appliance on and off WiFi	
7.2.3	Temperature	11
7.2.5 7.2.6	Temperature unit SabbathMode	
7.2.0	HumiditySelect	. 12
7.2.8 7.2.9	Presentation light *	12
7.2.9	Display brightness Door alarm	13
7.2.11 7.2.12	Alarm Sound	
7.2.12	Key Sound Display lock	14
7.2.14 7.2.15	Access codes	
7.2.15	Language Device information	15 15
7.2.17 7.2.18	Software Reminder	
7.2.10	Resetting to factory settings	
7.3 7.3.1	Message	16
7.3.2	Warnings Reminders	
8	Features	18
8.1 8.2	Safety lock Labels	18 19
9.2	Maintenance	19
9.1	Air exchange through the FreshAir activated	
9.2	charcoal filter Cleaning the appliance	19 19
10	Customer help	20
10.1	Technical specifications	20
10.2 10.3	Operating noises Technical fault	20 20
10.4	Customer Service	21
10.5	Model plate	22
11	Shutting down	22
<b>12</b> 12.1	Disposal Preparing appliance for disposal	<b>22</b> 22

#### 

The manufacturer is continually working on the further development of all types and models. Please be aware that we reserve the right to make changes to the shape, equipment and technology.

Symbol	Explanation	
	<b>Read instructions</b> Please read the information in these instruc- tions carefully to understand all of the benefits of your new appliance.	
	Additional information on the Internet The digital manual with additional informa- tion and in other languages can be found via the QR code on the front of the manual or by entering the service number at home.liebherr.com/fridge-manuals. The service number can be found on the serial tag:	
	Fig. Example illustration	
	<b>Check appliance</b> Check all parts for transport damage. If you have any complaints, please contact your agent or customer service.	
*	<b>Differences</b> These instructions apply to a range of models, so differences are possible. Sections that apply to certain models only are marked with an asterisk (*).	
$\land$	Instructions and results Instructions are marked with a ▶. Results are marked with a ▷.	
	<b>Videos</b> Videos about the appliances are available on the YouTube channels of Liebherr-Hausgeräte.	

#### Open source licences:

The appliance contains software components that use open source licences. Information on the open source licences used can be found here: home.liebherr.com/ open-source-licences

These operating instructions apply to:

UWpri	3661
	3662
	3672
	3761
	3762
	3782
UWgbi	3682
	3782

# 1 Appliance at a glance

# 1.1 Scope of delivery

Check all parts for transport damage. Contact your dealer or customer service in the event of complaints. (see 10.4 Customer Service)

Your new appliance comes with the following parts:

- Built-in appliance
- Features (depending on the model)
- Installation materials (depending on the model)
- "Quick Start Guide"
- "Installation Guide"
- Service Brochure

# 1.2 Overview of the appliance and equipment




Fig. 1 Example illustration, front end

Equipment

(1) Type plate	(5) Condensation drainage
(2) Shelves	(6) Controls and tempera-
	ture display

(3) Adjustable feet (4) Interior lighting\*

(7) FreshAir activated carbon filter (8) Lock\*





Fig. 2 Example illustration, front end

#### Equipment

- (1) Type plate (2) Shelves
- (3) Adjustable feet
- (4) Interior lighting\*
- (5) Condensation drainage (6) Controls and temperature display (7) FreshAir activated
- carbon filter (8) Lock\*



- Fig. 3 Example illustration, front end
- (1) Type plate (2) Shelves
- (3) Adjustable feet
- (5) Condensation drainage (6) Controls and tempera-

Equipment

- ture display
- (7) FreshAir activated carbon filter
- (4) Interior lighting\*

## 1.3 SmartDevice

SmartDevice is the networking solution for your wine storage cabinet.

If your appliance SmartDevice-enabled or compatible, you can quickly and easily connect your appliance to your WiFi. With the SmartDevice app, you can operate your appliance from a mobile device. Additional functions and setting options are available in the SmartDevice SmartDevice app.

SmartDevice-

Your appliance is capable of being a appli- SmartDevice. To be able to connect your device to WiFi, you need to download the SmartDevice app.\*

ance:\*

Your appliance is compatible for use compatible appli- with the SmartDeviceBox. You must first purchase and install the Smart-DeviceBox. In order to connect your appliance to the WiFi, you need to download the SmartDevice app.\*



Purchasing

SmartDeviceBox

Hausgeräte store:\*

Downloading the SmartDevice app:

information smartdevice.liebherr.com More about SmartDevice:

the home.liebherr.com/shop/de/deu/ smartdevicebox.html\* in the Liebherr-



After installing and configuring the SmartDevice, you can connect your appliance to the WiFi using the SmartDevice app and the WiFi appliance function (see 7.2.3 WiFi).

enabled ance:\*

SmartDevice-

# **General safety instructions**

#### Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan. You cannot use the SmartDeviceBox.\*

## 1.4 Appliance range of use

#### Intended use

The appliance is only suitable for storing wine in a domestic or domestic-like environment. This includes, for example, using

- in staff kitchens, bed and breakfast establishments,
- by guests in country houses, hotels, motels and other accommodation,
- for catering and similar services in the wholesale trade.

The appliance is not suitable for freezing food;

The appliance is suitable for integrating under counters.

All other types of use are not permitted.

#### Foreseeable misuse

The following applications are expressly forbidden:

- Storing and refrigerating medicines, blood plasma, laboratory preparations or similar substances and products based on the Medical Device Directive 2007/47/EC
- Use in outdoor areas with very high humidity
- Use in areas at risk of explosions

Misusing the appliance may lead to damage to the goods stored or they may spoil.

#### **Climate classifications**

Depending on the climate classification the appliance is designed to operate in restricted ambient temperatures. The climate classification applying to your appliance is printed on the rating plate.

#### Note

Keep to the specified ambient temperatures in order to guarantee that the appliance works properly.

Climate clas- sification	for ambient temperatures of
SN	10 °C to 32 °C
N	16 °C to 32 °C
ST	16 °C to 38 °C
Т	16 °C to 43 °C
SN-ST	10 °C to 38 °C
SN-T	10 °C to 43 °C

## 1.5 Conformity

The refrigerant circuit has been tested for leaks. When installed, the appliance complies with the applicable safety regulations and with the corresponding directives.

For the market:*	EU The appliance complies 2014/53/EU.*	with directive
For the market:*	GB The appliance complies Equipment Regulations No. 1206.*	

The full text of the EU Declaration of Conformity is available on the following website: www.Liebherr.com

Since there are no energy efficiency guidelines for wine cooling appliances, wine compartments are considered to be cellar compartments for assignment to an energy efficiency class.

## **1.6 SVHC substances according to REACH regulation**

You can check whether your appliance contains SVHC substances according to REACH regulation at the following link: home.liebherr.com/de/deu/de/liebherr-erleben/nach-haltigkeit/umwelt/scip/scip.html

### 1.7 EPREL database

Details about energy labelling and ecodesign requirements will be available on the European product database (EPREL) from 1st March 2021. You can access the product database at the following link: https://eprel.ec.europa.eu/ You will be asked to enter the model ID. You can find the model ID on the nameplate.

## 1.8 Spare parts

The spare parts availability for functional parts and stockable parts of the equipment is 15 years.

# 2 General safety instructions

Please keep these operating instructions in a safe place so you can refer back to them at any time.

If you pass the appliance on, please hand these operating instructions to the next user.

Read these operating instructions carefully before use to ensure safe and correct use of the appliance. Follow the instructions, safety instructions and warning messages included at all times. They are important for ensuring you can operate and install the appliance safely and without any problems.

#### Danger for the user:

 This device can be used by children and people with impaired physical, sensory or mental abilities or with a lack of experience and knowledge provided that they are supervised or have received instruction in the safe use of this device, and about the resulting hazards. Children must not play with this appliance. Cleaning and user maintenance work must not be carried out by children without adult supervision. Children aged between 3 and 8 are allowed to load and unload the appliance. Children below the age of 3 must be kept away from the appliance unless they are under continuous adult supervision.

- The socket must be easily accessible so that the appliance can be disconnected quickly from the electricity in an emergency. It must not be located in the area behind the appliance.
- When disconnecting the appliance from the supply, always take hold of the plug. Do not pull the cable.
- In the event of a fault pull out the mains plug or deactivate the fuse.
- Do not damage the mains power cable. Do not operate the appliance with a defective mains power cable.
- Only customer service or other specially trained staff may repair or perform other operations on the appliance.
- Only install, connect and dispose of the appliance according to the instructions.
- Only use the appliance when is installed.

# Fire hazard:

- The coolant used (information on the model plate) is ecofriendly but also flammable. Any leaking coolant may ignite.
  - Do not damage the refrigerant circuit pipes.
  - Do not handle ignition sources inside the appliance.
  - Do not use electrical appliances inside the appliance (e.g. steam cleaners, heaters, ice cream makers, etc.).
  - If the refrigerant leaks: remove any naked flames or ignition sources from the vicinity of the leakage point. Properly air the room. Inform customer services.
- Do not store explosives or sprays using combustible propellants such as butane, propane, pentane, etc. in the appliance. To identify these spray cans, look for the list of contents printed on the can, or a flame symbol. Gases possibly escaping may ignite due to electrical components.
- Keep burning candles, lamps and other items with naked flames away from the appliance so that they do not set the appliance on fire.
- Please be sure to store alcoholic drinks or other packaging containing alcohol in tightly closed containers. Any alcohol that

leaks out may be ignited by electrical components.

# Danger of tipping and falling:

- Do not misuse the plinth, drawers, doors etc. as a step or for support. This applies particularly to children.

# Danger of food poisoning:

- Do not consume food which has been stored too long.

# Danger of frostbite, numbness and pain:

 Avoid prolonged skin contact with cold surfaces or refrigerated/frozen goods or take protective measures, e.g wear gloves.

## Danger of injury and damage:

- Hot steam can lead to injury. Do not use electrical heating or steam cleaning equipment, open flames or defrosting sprays to defrost.
- Do not use sharp implements to remove the ice.

# **Risk of crushing:**

Do not hold the hinge when opening and closing the door. Fingers may get caught.

# Symbols on the appliance:



This symbol may be located on the compressor. It relates to the oil in the compressor and makes reference to the risk that: Swallowing or inhaling can be fatal. This advice is only relevant to recycling. There is no danger in normal operation.



This symbol is located on the compressor and indicates the danger of flammable materials. Do not remove the sticker.



This or a similar sticker may be located on the rear of the appliance. This sticker indicates that there are vacuum insulation panels (VIP) or perlite panels in the door and/or housing. This advice is only relevant to recycling. Do not remove the sticker.

# Please note the warning messages and other specific advice in the other chapters:

	DANGER	indicates an immediately hazardous situation which will lead to death or serious injuries if it is not avoided.
$\triangle$	WARNING	indicates a hazardous situation which may lead to death or serious injuries if it is not avoided.
	CAUTION	indicates a hazardous situation which may lead to minor or moderate injuries if it is not avoided.

# Functionality of the Touch & Swipe display

NOTICE	indicates a hazardous situation which may lead to damage to property if it is not avoided.
Note	indicates useful instructions and tips.

# 3 Functionality of the Touch & Swipe display

You operate your appliance using the Touch & Swipe display. You select appliance functions in the Touch & Swipe display (hereafter referred to as display) by tapping them. If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.

# 3.1 Navigation and symbol explanation

In the illustrations, different symbols are used to navigate the display. The following table describes these symbols.

Symbol	Description
	<b>Briefly touch the display:</b> Activates/deactivates function. Confirms selection. Opens submenu.
(35)	Touch the display for a specified time (e.g. 3 seconds): Activates/deactivates function or value.
	<b>Swipe left or right:</b> Navigate in the menu.
Back	Briefly touch the Back symbol: Jumps back one menu level.
Back (35)	Press and hold the Back symbol for 3 seconds: Jumps back to the status display.
 	Briefly touch the Back symbol at the top left: Jumps back one menu level.
<ul> <li>➡</li> <li>○</li> </ul>	Arrow with clock: It takes more than 10 seconds for the following message to appear in the display.
<ul> <li>▶ ▶ ▶</li> <li>2s 5s 10s</li> </ul>	Arrow with a time indication: It takes the specified amount of time until the following message appears in the display.

<ul> <li>pen Settings menu" symbol:</li> <li>vigates to the Settings menu and ens the settings menu.</li> <li>necessary: Navigate to the desired action in the Settings menu.</li> <li>e 3.2.1 Opening the Settings menu)</li> <li>pen Advanced menu" symbol:</li> <li>vigates to the Advanced menu and ens the advanced menu.</li> <li>necessary: Navigate to the desired mection in the Advanced menu.</li> </ul>
ens the settings menu. necessary: Navigate to the desired action in the Settings menu. e 3.2.1 Opening the Settings menu) pen Advanced menu" symbol: vigates to the Advanced menu and ens the advanced menu. necessary: Navigate to the desired
action in the Settings menu. e 3.2.1 Opening the Settings menu) pen Advanced menu" symbol: vigates to the Advanced menu and ens the advanced menu. necessary: Navigate to the desired
pen Advanced menu" symbol: vigates to the Advanced menu and ens the advanced menu. necessary: Navigate to the desired
vigates to the Advanced menu and ens the advanced menu. necessary: Navigate to the desired
ens the advanced menu. necessary: Navigate to the desired
e 3.2.2 Opening the expanded nu)
you do not perform any action on e display for 10 seconds, the display her jumps back to the higher-level nu or directly to the status display.
you open the door and immedi- ly close it again, the display jumps ectly back to the status display.

# 3.2 Menus

The appliance functions are distributed over various menus:

Menu	Description
Main menu	When you switch the appliance on, you are automatically in the main menu.
	From here you can navigate to the most important appliance functions, to the Settings menu and to the Advanced menu.
کې Settings	The Settings menu contains additional appliance functions for setting up your appliance.
Settings menu	
НСМ	The advanced menu contains special appliance functions for setting up your appliance. Access to the Advanced menu is protected by the numerical code <b>151</b> .
Advanced menu	

### 3.2.1 Opening the Settings menu




Fig. 4 Example illustration

- Carry out action steps according to the illustration.
- $\triangleright$  Settings menu is open.
- ► If necessary: Navigate to the desired function.

# **Putting into operation**

### 3.2.2 Opening the expanded menu




Fig. 5 Access with numerical code 151

- Carry out action steps according to the illustration.
- ▷ The expanded menu is open.
- ► If necessary: Navigate to the desired function.

# 3.3 Sleep mode

If you do not touch the display for 1 minute, the display switches to sleep mode. In sleep mode, the display brightness is dimmed.

### 3.3.1 Ending sleep mode

► Touch the display briefly with your finger.

 $\triangleright$  Sleep mode is ended.

# 4 Putting into operation

# 4.1 Switching on appliance (first use)

Ensure that the following requirements are met:

- Appliance is installed and connected.
- All adhesive strips, adhesive and protective films and transport locks are removed from inside and outside the appliance.



Fig. 6 Example illustration

- The standby symbol is flashing: Wait until the start process is complete.
- Dash The display shows the standby symbol.

If the appliance has been supplied with factory settings, the screen language and the date/time first need to be set when using the appliance for the first time.




Fig. 7

Carry out action steps according to the illustration.
 Language is set.



Fig. 9 Status display



- Fig. 9 Status display
- > The appliance is ready for operation once the temperature appears in the display.
- The temperature display flashes until the set temperature is reached.

# 5 Storage

# 5.1 Information regarding storage



Do not use any electrical appliances in the food area of the appliance unless recommended by the manufacturer.

#### Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient. ► Always keep air slots clear.

Observe the following specifications for storage:

- Keep the air vents on the fan free.

# 5.2 Storage sketch

#### 5.2.1 UWpri 3761




Fig. 10 Total 44 bottles (0.75 l Bordeaux bottles as per standard NF H 35-124)

### 5.2.2 UWpri 3661





Fig. 11 Total 44 bottles (0.75 l Bordeaux bottles as per standard NF H 35-124)



### 5.2.3 UWpri 3662 / UWpri 3672 / UWgbi 3682

Fig. 12 Total 32 bottles (0.75 l Bordeaux bottles as per standard NF H 35-124)

# 

5.2.4 UWpri 3762 / UWpri 3782 / UWgbi 3782

Fig. 13 Total 38 bottles (0.75 l Bordeaux bottles as per standard NF H 35-124)

# 6 Saving energy

- Pay attention to good ventilation. Do not cover ventilation holes or grids.
- Always keep the fan air slits clear.
- Do not install the appliance in direct sunlight or near radiators or similar sources of heat.
- If the appliance is installed directly next to an oven, the energy consumption may increase slightly. This is dependent on the service life and usage intensity of the oven.
- Energy consumption depends on the installation conditions, e.g. the ambient temperature (see 1.4 Appliance range of use) . A warmer ambient temperature can increase the energy consumption.
- Open the appliance for as short a time as possible.
- The lower the temperature is set the higher the energy consumption.

# 7 Controls

# 7.1 Control and display elements


The display provides a quick overview of the current appliance status, the temperature setting, the status of functions and settings as well as alarm and error messages.

Operation takes place directly on the Touch & Swipe display by swiping and touching.

Functions can be activated or deactivated and setting values can be changed.



*Fig. 14 Touch & Swipe display\** (1) Status display



*Fig. 15 Touch & Swipe display\** (1) Status display

### 7.1.1 Status display



*Fig. 16 Status display\** (1) Temperature



*Fig. 17 Status display\** (1) Temperature

The status display is the output display.

Navigation to the functions takes place from the status display.

## 7.1.2 Display symbols

Display symbols provide information about the status of the appliance.

Symbol	Appliance status
Ċ	<b>Standby symbol</b> Appliance is switched off.
	Standby (flashing)symbolAppliance is starting up.
	<b>Temperature (flashing)</b> Target temperature not yet reached. Appliance cooling to temperature set.
Device failure	<b>Error symbol (red)</b> Appliance is in error state.
	Background (blue) Active setting or active function
	<b>Bar (increasing)</b> Press for 3 seconds to activate setting.
	Bar (decreasing) Press for 3 seconds to deactivate setting.

Symbols on the status display

#### 7.1.3 Acoustic signals

A signal sounds in the following cases:

- If a function or a value is confirmed.
- If a function or a value can either not be activated or not deactivated.
- As soon as an error occurs.
- If there is an alarm message.

The alarms can be switched on and off in the customer menu.

# 7.2 Appliance functions

#### 7.2.1 Notes on the appliance functions

The appliance functions are set at the factory so that your appliance is fully functional.

Before you alter, activate or deactivate the device functions, make sure that the following requirements are met:

- □ You have read and understood the descriptions of how the display works. (see 3 Functionality of the Touch & Swipe display)
- You have familiarised yourself with the operating and display elements of your appliance. (see 7.1 Control and display elements)

### 7.2.2 Switching appliance on and off



This function makes it possible to switch the entire appliance on and off.

#### Switching on appliance If demo mode is not activated:





Fig. 18

• Carry out action steps according to the illustration.

#### If demo mode is activated:



#### Fig. 19

• Carry out action steps according to the illustration.

#### Note

Deactivate demo mode before the countdown has finished.



Fig. 21 Status display



- Fig. 21 Status display
- $\triangleright$  The temperature appears in the display.

#### Switching off appliance



Fig. 22




Fig. 23

- Carry out action steps according to the illustration.
- $\triangleright$  Standby symbol is shown in the display.
- D The display switches off automatically after around 10 minutes.



Use this function to connect your appliance to WiFi. You can then operate it via the SmartDevice app on a mobile device. You can also use this function to disconnect or reset the WiFi connection.

To connect your device to WiFi, you need the SmartDeviceBox.\*

More information on the SmartDevice: (see 1.3 SmartDevice)

#### Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan.

You cannot use the SmartDeviceBox.\*

#### Establishing the WiFi connection for the first time

Make sure that the following requirements are fulfilled:

- □ You have purchased and inserted a SmartDeviceBox. (see 1.3 SmartDevice) \*
- You have installed the SmartDevice app (see apps.home.liebherr.com).
- Registration in the SmartDevice app is completed.








Fig. 25

Carry out action steps according to the illustration.
 Connection is established.

Disconnecting from the WiFi



Fig. 26





Fig. 27

- Carry out action steps according to the illustration.
- $\triangleright$  There is no connection.

#### **Resetting the WiFi connection**



Fig. 28





- Carry out action steps according to the illustration.
- WiFi connection and other WiFi settings are reset to factory settings.

#### Showing information about the WiFi connection



Fig. 30




Fig. 31



Fig. 32 Status display



Fig. 32 Status display

Carry out action steps according to the illustration.



The temperature depends on the following factors:

- How often the door is opened
- How long the door is open for
- The room temperature of the installation site
- The type, temperature and amount of refrigerated food

#### Note


The temperature may differ from the temperature displayed in some areas of the interior.

At the correct temperature, cooled produce will keep for longer. This avoids disposing of food unnecessarily.

#### Setting temperature

The following steps describe how to increase the temperature, e.g. from 5 °C to 10 °C.

- Tap the temperature.\*
- ► Tap the temperature of the desired zone.\*



#### Fig. 33 \*




Fig. 34 \*

Carry out action steps according to the illustration.

Temperature is set.  $\triangleright$ 



Use this function to set the temperature unit. You can set degrees Celsius or degrees Fahrenheit as the temperature unit.

Fig. 35

Setting the temperature unit

Carry out action steps according to the illustration.  $\triangleright$  The temperature unit is set.



# 7.2.6 SabbathMode

You can use this function to activate or deactivate SabbathMode. If you activate this function, some electronic functions are switched off. As a result, your device meets the religious requirements for Jewish holidays such as Sabbath and complies with STAR-K Kosher certification.

Device status when SabbathMode is active

The status display shows SabbathMode permanently.

All functions on the display are locked except for the Deactivate SabbathMode function.

Active functions remain active.

The display remains bright when you close the door.

The interior lighting is deactivated.

Reminders are not implemented. The set time interval stops.

Reminders and warnings are not displayed.

There is no door alarm.

There is no temperature alarm.

After a power failure, the appliance returns to SabbathMode. Device status

#### Note

This appliance has certification from the "Institute for Science and Halacha". (www.machonhalacha.co.il)

You can find a list of STAR-K-certified appliances at www.star-k.org/appliances.

#### Activating SabbathMode



Fig. 37



Fig. 38

- Carry out action steps according to the illustration.
- $\triangleright$ SabbathMode is activated.

▷ The status display shows SabbathMode permanently.

#### Deactivating SabbathMode

The SabbathMode is automatically deactivated after 80 hours. However, you can also deactivate SabbathMode manually at any time:



Fig. 39

- Carry out action steps according to the illustration.
- $\triangleright$  SabbathMode is deactivated.



Use this function to set the humidity inside your appliance. Setting the humidity correctly will have a positive effect on the structure of the corks during long-term storage and prevent them from drying out.

#### Note

The frequency and duration for which the door is open influence the humidity in the appliance.

You can choose between two humidity settings:

HumiditySe- lect function	Temperature setting on the appli- ance	
Standard (preset)	10-12 °C	average humidity in the envi- ronment between 50-80% low energy consumption of the appliance
High	10-12 °C	average humidity in the envi- ronment < 50% energy consumption of the appliance increases

#### Increasing the humidity in the appliance



Fig. 40




Fig. 41

Carry out action steps according to the illustration.
 Humidity in the appliance increases.

#### Setting the humidity in the appliance to standard



Fig. 42




Fig. 43

- ► Carry out action steps according to the illustration.
- $\triangleright$  Humidity in the appliance decreases.



This setting allows the presentation light to be adjusted incrementally.

The following brightness values can be set:

- Off
- 20%
- 40%
- 60%
- 80%
- 100% (default)

#### Adjusting the presentation light

The following steps describe how to reduce the brightness of the presentation light, e.g. from 100 % to 40 %.



Fig. 44




Fig. 45

- Carry out action steps according to the illustration.
- The brightness of the presentation light changes accordingly.



#### Use this function to set the display brightness in stages.

You can select the following brightness levels:

- 40 %
- 60 %
- 80%
- 100 % (pre-setting)

#### Setting the brightness



Fig. 46




Fig. 47 Example illustration: Switch from 80 % to 60 %.
Carry out action steps according to the illustration.

 $\triangleright$  The brightness is set.



Use this function to activate or deactivate the door alarm. The door alarm sounds if the door is open for too long. The door alarm is activated on delivery. You can set how long the door may be open before the door alarm sounds.

The following values can be set:

- 1 minute
- 2 minutes
- 3 minutes
- Off

#### Setting the door alarm





Fig. 48



*Fig. 49 Example illustration: Change door alarm from 1 minute to 3 minutes.* 

Carry out action steps according to the illustration.
 The door alarm is set.

#### Deactivating the door alarm



Fig. 51




Fig. 52

• Carry out action steps according to the illustration.

 $\triangleright$  The door alarm is deactivated.



This function enables all alarm sounds, such as door alarms, to be switched on and off.

#### Activating Alarm Sound



#### Fig. 53



Fig. 54

Carry out action steps according to the illustration.
 Alarm Sound is activated.

#### Deactivating Alarm Sound



Fig. 55



Fig. 56

• Carry out action steps according to the illustration.

 $\triangleright$  Alarm Sound is deactivated.



This function makes it possible to switch all button sounds, confirmation sounds, and the startup sound on and off.

#### Activating Key Sound



Fig. 57




Fig. 58

- Carry out action steps according to the illustration.
   Key Sound is activated.
- Deactivating Key Sound



#### Fig. 59




Fig. 60

- Carry out action steps according to the illustration.
- ▷ Key Sound is deactivated.



This setting avoids accidental operation of the appliance.

Application:

- Prevent settings and functions being changed unintentionally.
- Prevent appliance being switched off unintentionally.
- Prevent temperature being set unintentionally.

#### Activating display lock




Fig. 61




Fig. 62

- Carry out action steps according to the illustration.
- $\triangleright$  The display lock is activated.
- $\triangleright$  The status display appears.

Unlocking the display for a short time




Fig. 63 \*




Fig. 64 \*

- Carry out action steps according to the illustration.
- $\triangleright$  The display lock is deactivated.
- $\triangleright$  The status display appears.

### 7.2.14 Access codes

Various settings are possible.

Application:

- Changing the display lock code.
- Resetting the display lock code.



#### Changing display lock code

This setting allows the code for the display lock to be changed.

The setting is made in 3 stages:

- Entering of old code
- Entering of new code
- Confirming of new code

#### Note

In the following example, the default factory-set code 1 1 1 is changed.

The new code is: 2 3 4 5



Fig. 65




Fig. 66

- Carry out action steps according to the illustration.
- $\triangleright$  Entry of the old code successful.





Fig. 67

- Carry out action steps according to the illustration.
- $\triangleright$  Entry of the new code successful.



#### Fig. 68

- Carry out action steps according to the illustration.
- ▷ Confirmation of the new code successful.
- $\triangleright$  The code has been changed.

#### Resetting display lock code

Code forgotten or not known.

- Reset appliance to factory settings. (see 7.2.19 Resetting to factory settings )
- $\triangleright$  The appliance is reset to the original settings.
- ▷ The factory-set code is: **1 1 1 1**




This setting allows the display language to be set.

#### Setting language



Fig. 69



#### Fig. 70

- Carry out action steps according to the illustration.
- Dash The selected language is set.

# 7.2.16 Device information



Use this function to indicate the model name, index, serial number and service number of your device. You will need the device information when you contact customer service. (see 10.4 Customer Service)

This function also opens the Advanced menu. (see 3 Functionality of the Touch & Swipe display)

#### Indicating the device information



Fig. 71



Fig. 72

- Carry out action steps according to the illustration.
- $\triangleright$  Display indicates device information.



Use this function to indicate the software version of your device.  $\label{eq:constraint}$ 

#### Indicating the software version



Fig. 73



Fig. 74

- Carry out action steps according to the illustration.
- ▷ Display indicates software version.



This function allows you to activate or deactivate the reminder to change the FreshAir activated charcoal filter.

#### Deactivating the reminder

7.2.18 Reminder



Fig. 75



Fig. 76

- Carry out steps according to the illustration.
- ▷ Reminder is deactivated.

#### Activating the reminder



Fig. 77



Fig. 78

- Carry out steps according to the illustration.
- ▷ Reminder is activated.



#### 7.2.19 Resetting to factory settings

Use this function to reset all settings to factory defaults. All settings you have made so far are reset to their original settings.

#### Performing a reset



Fig. 79




Fig. 80

- Carry out action steps according to the illustration. ►
- $\triangleright$  Device is reset.
- $\triangleright$  Device is switched off.
- Restart the device. (see 4.1 Switching on appliance (first use))

# 7.3 Message

### 7.3.1 Warnings

Warnings are issued by means of an acoustic signal and visually via a symbol on the display. The signal gets louder until the warning is acknowledged.

Message (red)	Cause	Remedy
Close the door Door open	This message appears if the door is open for too long.	Close the door. Tap briefly. Alarm is stopped. <b>Note</b> The time until the message appears can be set. (see 7.2.10 Door alarm )

Message (red)	Cause	Remedy
Temperature alarm	This message appears if the temperature does not match the set temperature. Reasons for differences in temperature can be: Warm produce for cooling has been placed inside. Too much warm air has got in while you were sorting out the freezer or removing items. The power was cut off for a prolonged period.	Tap briefly. Information about errors and appliance status are displayed. Tap briefly. Warmest/coldest temperature, date and time are displayed. Tap briefly. The status screen is displayed. The current temperature and the alarm symbol flash red until the set temperature is reached.
Device failure	The appliance is faulty, there is an appli- ance error or a component of the appliance has a fault.	Check the quality of the refrigerated goods. Store the cooled produce elsewhere. Tap briefly. The error code (e.g. BT021) is xy00           Please move goods to another fridge.           Image: Store the store fridge.
		Tap briefly. A further error code is displayed if there is one or Status screen is displayed with flashing error symbol. Swiping or tapping the display will show the error code(s) again. Make a note of error code(s) and contact
Power failure Power cut	The message appears following an inter- ruption to the electricity supply.	Customer Service. (see 10.4 Customer Service) Tap briefly. Battery's state of charge, information about errors and appliance status are displayed Tap briefly. The warmest temperature and the period of power interruptions are displayed. Tap briefly. The status screen is displayed. The current temperature and the alarm symbol flash red until the set temperature is reached. Check the quality of the refrigerated goods.
WiFi error WiFi error	Wi-Fi connection is interrupted.	Check connection. Press briefly. Alarm is stopped.
WWW error WWW error, WiFi	This message appears if there is no internet connection via WiFi.	Check connection. Press briefly. Alarm is stopped.

#### 7.3.2 Reminders

Reminders appear when you are being asked to do something. The are issued by means of an acoustic signal and visually via a symbol on the display. Acknowledge the message by pressing the confirmation button.

# Features

Message (yellow)		Cause	Remedy	
FreshAir filter		The message appears every 6 months.	ReplaceFreshAir activated charcoal filter, Press briefly. Reminder is closed.	
ReplaceFresh vated charcoa				

# 8 Features

# 8.1 Safety lock

The lock in the appliance door is equipped with a safety mechanism.

### 8.1.1 Locking appliance



Fig. 81 Example illustration

- Insert key.
   Turp key optiolo
- ► Turn key anticlockwise by 90°.
- $\triangleright$  The appliance is locked.

### 8.1.2 Unlocking appliance



Fig. 82 Example illustration

- ▶ Insert key *Fig. 82 (1)*.
- ▶ Turn key clockwise by 90° Fig. 82 (2).
   ▷ The appliance is unlocked.

### 8.1.3 Locking appliance

## Lock freezer compartment.

- Insert key.
- Turn key clockwise by 45°.
- $\triangleright$  The freezer compartment is locked.

#### Lock freezer and fridge compartment.

- Insert key.
- ► Turn key clockwise by 90°.
- > The freezer and fridge compartment is locked.

### 8.1.4 Unlocking appliance

#### Unlock fridge compartment.

- Insert key.
- ▶ Turn key anticlockwise by 45°.
- $\triangleright$  The fridge compartment is unlocked.

#### Unlock freezer and fridge compartment.

- Insert key.
- ► Turn key anticlockwise by 90°.
- $\triangleright$  The freezer and fridge compartment is unlocked.

### 8.1.4 TipOpen


TipOpen is a door opening aid that only works when the appliance is in operation.

#### NOTICE

Risk of damage due to blocking of the door opening aid! Defective door opening aid. If something is blocking the door opening aid, you will hear a loud clacking noise. If this happens repeatedly, you may permanently damage the door opening aid.


Do not block the door opening aid.

### 8.1.4 Opening the door



#### Fig. 83

Door opening on the left-hand side: Press the top left door slightly inwards and release.



#### Fig. 84

- ▷ Push rod *Fig. 84 (1)* opens door approximately 7 cm.
- Open the door fully by hand within three seconds to prevent it from closing automatically.

#### 8.1.4 Closing the door

Ensure that the following requirement is met:

- Push rod is retracted.
- Close the door.

### 8.1.4 Resetting TipOpen

If something is blocking the door opening aid, the push rod can no longer reach its starting position. To ensure that TipOpen continues to work, TipOpen must be reset

- Remove mains plug.
- ► Wait about five seconds.
- Insert plug.
- $\triangleright$  The push rod moves to the starting position and is flush with the front of the appliance.

# 8.2 Labels

Description labels as accessories can be purchased from your specialist dealer. You can use these to note the types of wine that are stored in the respective compartment.




Fig. 85

Attach the label from above.

# 9 Maintenance

# 9.1 Air exchange through the FreshAir activated charcoal filter


Wine is constantly developing according to its ambient conditions, so air quality is essential for preservation. The FreshAir activated charcoal filter guarantees optimal air quality.

- □ Change the activated charcoal filter every 6 months.
- Dispose of the activated charcoal filter with regular household waste.

#### Note

FreshAir activated charcoal filters can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/zubehor.html.

# **9.1.1** Replacing the FreshAir activated charcoal filter



- Fig. 86 Example illustration
- Press the filter holder in, release it again and pull it out.




Fig. 87 Example illustrationRemove the old filter from the holder.





Fig. 88 Example illustrationSnap the new filter into the holder.



- Fig. 89 Example illustration
- Press the filter holder in as far as it will go and release.
   FreshAir activated charcoal filter has been changed.

# 9.2 Cleaning the appliance

### 9.2.1 Ready

#### Danger of electric shock!

Remove the refrigerator connector or interrupt the power supply.

# Customer help

# 

Risk of fire

Do not damage the refrigeration circuit.

- Empty the appliance.
- Remove mains connector.

#### 9.2.2 Cleaning the interior

#### NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.
- Plastic surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Metal surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Drain hole: remove deposits using a thin item (for example a cotton bud).

#### 9.2.3 Clean the components

#### NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

#### Clean with a damp cloth:

- Retractable rails
  - Please note: The grease in the tracks is used for lubrication and must not be removed!
- ► To disassemble components: see the relevant section.
- Clean the components.

#### 9.2.4 After cleaning

- ▶ Wipe the appliance and the components dry.
- Connect and switch on the appliance.
- Repeat cleaning regularly.

# 10 Customer help

# 10.1 Technical specifications

Lighting	
Class <sup>1</sup>	Light source
This product contains one or more energy efficiency class F light sources.	LED
This product contains one or more energy efficiency class G light sources.	LED

<sup>1</sup> The appliance may contain light sources with different energy efficiency classes. The lowest energy efficiency class is indicated.

For appliances with a WiFi connection:\*

Frequency specification*		
Frequency band	2.4 GHz	
Maximum radiated power	< 100 mW	
Purpose of the wireless equipment	Integration in the local WiFi network for data communication	

# 10.2 Operating noises

The appliance makes different noises when it is on.

- At higher temperatures the appliance uses less energy but works for longer. It is quieter.
- At lower temperatures the food is cooled faster. It is louder.

#### Examples:

- Functions on (see 7.2 Appliance functions)
- Fan running
- Food recently added
- High ambient temperature
- Door open for a while

Noise		Possible cause		Type of noise			
Bubbling splashing	and	Coolant into the circuit.	flowing cooling	Nori nois		opera	ting
Hissing		Coolant into the circuit.	sprays cooling	Nori nois	mal se	opera	ting
Humming		The appliance is cooling. The volume depends on the cooling output.		Normal operating noise			
Suction noises		Soft-closing door is being opened and closed.		Normal operating noise			
Humming and rustling		The fan is running.		Normal operating noise		ting	
Clicking		Components are switched on and off.		1		ning	
Rattling or humming		Valves or flaps are working.		Normal switching noise		ning	
Noise	Poss	sible se	Type of no	oise	Lift	ing	
Vibration	Vibration Impl inst		Defective noise		inst	eck tallatio	the n.

			Level the appliance.
Rattling	Components, items inside the appliance	Defective noise	Secure components. Leave enough space between the items.

# 10.3 Technical fault

Your appliance is designed and built to ensure it works reliably and has a long service life. In the unlikely event that

a fault occurs during operation, please check whether it is due to an operating error. If so, you will be charged for the callout and repair costs even if it falls within the warranty period. You can fix the following faults yourself.

#### 10.3.1 Appliance function

Defect	Cause	Remedy
The appliance is	→ The appliance is not switched on.	<ul> <li>Switch the appliance on.</li> </ul>
not working.	→ The power plug is not properly plugged into the socket.	<ul> <li>Check the power plug.</li> </ul>
	→ There is something wrong with the power outlet fuse.	<ul> <li>Check the fuse.</li> </ul>
	→ Power cut	Keep the appliance closed.
	→ The IEC socket is not plugged into the appliance correctly.	<ul> <li>Check the IEC socket.</li> </ul>
Temperature is not cold enough.	→ The appliance door is not closed properly.	<ul> <li>Close the appliance door.</li> </ul>
	$\rightarrow$ Not enough ventilation.	<ul> <li>Keep ventilation grille clear, and clean it.</li> </ul>
	→ The ambient temperature is too high.	<ul> <li>Problem solution: (see 1.4 Appliance range of use)</li> </ul>
	→ The appliance was opened too many times or for too long.	<ul> <li>Wait to see if the required temperature corrects itself. If not, contact Customer Service. (see 10.4 Customer Service)</li> </ul>
	→ The temperature is set incorrectly.	► Turn down the temperature and check after 24 hours.
	→ The appliance is too close to a heat source (oven, radiator, etc).	Move the appliance or the heat source.
	→ The appliance was not correctly installed in the recess.	Check if the appliance was installed correctly and that the door closes properly.
The door seal is defective or needs to be replaced for another reason.	→ You can replace the door seal, depending on your model. It can be replaced without the need for special tools.	<ul> <li>Contact Customer Service. (see 10.4 Customer Service)</li> </ul>
The door seal is defective or needs to be replaced for another reason.	→ The door seal can be replaced. It can be replaced without the need for special tools.	<ul> <li>Contact Customer Service. (see 10.4 Customer Service)</li> </ul>
The appliance builds up too much ice or condensa- tion.	→ The door seal may have slipped out of its groove.	<ul> <li>Check that the door seal is well fitted in the groove.</li> </ul>

#### 10.3.2 Features

Defect	Cause	Remedy
The internal light	ightarrow The appliance is not switched on.	<ul> <li>Switch the appliance on.</li> </ul>
does not come on.	→ The door was open for longer than 15 minutes.	<ul> <li>Interior lighting switches off automatically after about 15 minutes when the door is open.</li> </ul>
	→ The LED interior light is faulty or the lid is damaged.	<ul> <li>Contact Customer Service. (see 10.4 Customer Service)</li> </ul>

### **10.4 Customer Service**

First check whether you can rectify the fault yourself (see 10 Customer help) . If you cannot rectify the problem, contact Customer Service.

You can find the address in the enclosed brochure "Liebherr-Service" or at home.liebherr.com/service.

# Shutting down

# WARNING

Unprofessional repair! Iniuries.

- ▶ Have any repairs and action not expressly specified on the appliance and mains cable carried out by service personnel only. (see 9 Maintenance)
- A damaged mains cable may only be replaced by the manufacturer, the manufacturer's Customer Service or a similarly qualified person.
- ▶ In the case of appliances with an IEC connector, the change may be made by the customer.

### 10.4.1 Contacting Customer Service

Make sure that the following appliance information is available:

□ Appliance name (model and index)

- □ Service no. (Service)
- Serial no. (S no.)
- Call up the appliance information via the display.
- -or-
- ▶ Refer to the type plate for appliance information. (see 10.5 Model plate)
- ▶ Note down the appliance information.
- Notify customer service: Report errors and the appliance information.
- $\triangleright$  This will help us to provide you with a faster, more accurate service.
- Follow further instructions from Customer Service.

# 10.5 Model plate

The type plate is located on the bottom inside of the machine.




Fig. 90

(1) Appliance description (3) Serial no. (2) Service no.

Note the data on the model plate.

# 11 Shutting down

- Empty the appliance.
- Switch off appliance. (see 7.2.2 Switching appliance on and off )
- Pull the mains plug out of the socket.
- Remove the IEC socket if required: Pull the IEC socket out of the appliance plug and move it to the left and right at the same time.
- Clean appliance. (see 9.2 Cleaning the appliance)
- ▶ Leave the door open, so that no unpleasant odours arise.

# 12 Disposal

# 12.1 Preparing appliance for disposal



Lamps

Liebherr uses batteries in some of its appliances. In the EU, for environmental reasons, legislation obliges the end user to remove these batteries before disposing of old appliances. If your appliance contains batteries, a corresponding notice is attached.

If you can remove the lamps yourself without destroying them, also remove these before disposal.

- ► Take the appliance out of operation.
- ▶ If possible: remove lamps without destroying them.

## 12.2 Disposing of the appliance in an environmentally friendly manner



The appliance still contains valuable materials and must be disposed of separately from unsorted municipal waste.



Lamps

For Germany:

Dispose of batteries separately from the old appliance. To do this, you can return the batteries free of charge to retailers as well as recycling centres and collection centres for recyclable materials.

Dispose of removed lamps via the respective collection systems.

You can dispose of the appliance free of charge via the class 1 collection containers at the local recycling and recyclable material collection centres. When purchasing a new fridge/freezer, if the sales area > 400 m<sup>2</sup>, retailers will also take back the old appliance free of charge.



Leaking coolant and oil!

Fire. The coolant contained in the appliance is eco-friendly, but also flammable. The oil contained in the appliance is flammable. Escaping coolant and oil can ignite if the concentration is high enough and in contact with an external heat source.

- Do not damage the pipelines of the coolant circuit and the compressor.
- Observe the notes on transporting the appliance.
- Transport the appliance without damaging it.
- Dispose of batteries, lamps and the appliance according to the above specifications.



home.liebherr.com/fridge-manuals

EN wine cooling cabinet

Issue date: 20250120

Part number index: 7083722-00

Liebherr-Hausgeräte GmbH Memminger Straße 77-79 88416 Ochsenhausen Deutschland