

## 

# Contents

<b>1</b> 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 <b>2</b>	Appliance at a glance Scope of delivery Overview of appliances and equipment SmartDevice Appliance range of use Conformity SVHC substances according to REACH regulation. EPREL database Spare parts General safety instructions	<b>3</b> 3 3 3 4 4 4 4 4 <b>4</b>
2	•	
<b>3</b> 3.1 3.2 3.3	Functionality of the Touch display Navigation and symbol explanation Menus Sleep mode	<b>6</b> 6 7
<b>4</b> 4.1 4.2	<b>Putting into operation</b> Switching on appliance (first use) Starting the EasyTwist-Ice for the first time*	<b>7</b> 7 7
<b>5</b> 5.1 5.2 5.3	<b>Storage</b> Information regarding storage Freezer compartment Storage times	<b>7</b> 7 8 8
6	Saving energy	8
<b>7</b> 7.1 7.1.1 7.1.2 7.2 7.2.1	Controls Controls and displays Status display Display symbols Appliance functions Notes on the appliance functions Switching the appliance off and on	9 9 9
$\widehat{(\widehat{\mathbf{n}})}$	WiFi	9
-18∵	Temperature	10
℃∕ℯ₣	Temperature unit	11
**	SuperFrost	11
*	Start defrosting cycle	11
ţvī Ţ	PartyMode	. 12
$\Psi$	SabbathMode	12
$\bigcirc$	E-Saver	13
-> <mark>0</mark> /-	Display brightness	13
	Door alarm	14
<td>Input lock</td> <td>14</td>	Input lock	14
Service No: Nocki Index: Serialit:	Device information	14
d SM: 300000000 PH SM: ALLIANDOOC Software	Software	
$\bigcirc$	Demo mode	15



## Resetting to factory settings......15

7.3 7.3.1 7.3.2 7.3.3	Messages Overview of warnings Ending warnings Overview of reminders	16
<b>8</b> 8.1 8.2 8.3 8.4	Features Drawers EasyTwist-Ice* VarioSpace Freezer pack*	<b>17</b> 17 18 19 19
<b>9</b> 9.1 9.2 9.3	Maintenance Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance	<b>19</b> 19 19 20
<b>10</b> 10.1 10.2 10.3 10.4 10.5	Customer help Technical specifications Operating noises Technical fault Customer Service Model plate	<b>22</b> 22 22 22 23 23
11	Shutting down	24
<b>12</b> 12.1 12.2	<b>Disposal</b> Preparing appliance for disposal Disposing of the appliance in an environmentally	<b>24</b> 24
	friendly manner	24

The manufacturer is continually working on the further development of all types and models. Please be aware that we reserve the right to make changes to the shape, equipment and technology.

Symbol	Explanation	
	<b>Read instructions</b> Please read the information in these instruc- tions carefully to understand all of the benefits of your new appliance.	
	Additional information on the Internet The digital manual with additional informa- tion and in other languages can be found via the QR code on the front of the manual or by entering the service number at home.liebherr.com/fridge-manuals. The service number can be found on the serial	
	tag:	
	Fig. Example illustration	
	Check appliance	
	Check all parts for transport damage. If you have any complaints, please contact your agent or customer service.	
*	<b>Differences</b> These instructions apply to a range of models, so differences are possible. Sections that apply to certain models only are marked with an asterisk (*).	



## ol Explanation

Instructions and results Instructions are marked with a ▶. Results are marked with a ▷.

#### Videos

Videos about the appliances are available on the YouTube channels of Liebherr-Hausgeräte.

#### Open source licences:

The appliance contains software components that use open source licences. Information on the open source licences used can be found here: home.liebherr.com/ open-source-licences

These operating instructions apply to:

FN	42 / 46 / 50 / 52(i) / 66 / 70 / 72
SFN	52
GN	42Ve04 / 46Ve05 / 50Ve06 / 52Ve07 / 42Vd24 / 46Vd25 / 50Vd26 / 52Vd2i
GNeu	1460 DI
SGN	52Vd27

#### Note

If your appliance has an N in its appliance designation, it is a NoFrost appliance.

# 1 Appliance at a glance

## 1.1 Scope of delivery

Check all parts for transport damage. Contact your dealer or customer service in the event of complaints. (see 10.4 Customer Service)

Your new appliance comes with the following parts:

- Standalone appliance
- Features (depending on the model)
- Installation materials (depending on the model)
- "Quick Start Guide"
- "Installation Guide"
- Service Brochure

# **1.2** Overview of appliances and equipment




Fig. 1 Example illustration

- (1) Controls
- (2) Type plate(3) Tilting drawer\*
- (4) SpaceBox\*
- (5) EasyTwist-Ice\*
- (7) Ice cube tray\*(8) NoFrost
- (9) Ventilation slit
- (10) VarioSpace
- (11) Adjustable feet (front), transport castors (rear), transport handles at the top (rear) and at the bottom (front)
- (6) Freezer tray\*, cold storage accumulators\*

Note

Shelves, drawers and baskets are arranged for optimum energy efficiency when the appliance is delivered. Changing how the shelves, for example, are inserted in the fridge compartment does not have any impact on energy consumption.

## 1.3 SmartDevice

SmartDevice is the networking solution for your freezer.

If your appliance SmartDevice-enabled or compatible, you can quickly and easily connect your appliance to your WiFi. With the SmartDevice app, you can operate your appliance from a mobile device. Additional functions and setting options are available in the SmartDevice SmartDevice app.

SmartDevice- enabled appli- ance:*	Your appliance is capable of being a SmartDevice. To be able to connect your device to WiFi, you need to download the SmartDevice app.*
SmartDevice- compatible appli- ance:*	Your appliance is compatible for use with the SmartDeviceBox. You must first purchase and install the Smart- DeviceBox. In order to connect your appliance to the WiFi, you need to

download the SmartDevice app.\*



More information **smartdevice.liebherr.com** about SmartDevice:

the home.liebherr.com/shop/de/deu/ Purchasing SmartDeviceBox in the Liebherr-Hausgeräte store:\*

Downloading the SmartDevice app:



smartdevicebox.html\*

After installing and configuring the SmartDevice, you can connect your appliance to the WiFi using the SmartDevice app and the WiFi appliance function (see WiFi).

## Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan.

You cannot use the SmartDeviceBox.\*

## 1.4 Appliance range of use

## Intended use

The appliance is only suitable for cooling food products in a domestic or household-like environment. This includes, for example, use:

- in staff kitchens, bed and breakfast establishments,
- by guests in country houses, hotels, motels and other accommodation.
- for catering and similar services in the wholesale trade.

The appliance is not suitable as a built-in unit.

All other types of use are not permitted.

## Foreseeable misuse

The following applications are expressly forbidden:

- Storing and refrigerating medicines, blood plasma, laboratory preparations or similar substances and products based on the Medical Device Directive 2007/47/EC
- Use in areas at risk of explosions

Misusing the appliance may lead to damage to the goods stored or they may spoil.

## **Climate classifications**

Depending on the climate classification the appliance is designed to operate in restricted ambient temperatures. The climate classification applying to your appliance is printed on the rating plate.

## Note

Keep to the specified ambient temperatures in order to guarantee that the appliance works properly.

Climate clas- sification	for ambient temperatures of
SN	10 °C to 32 °C
N	16 °C to 32 °C
ST	16 °C to 38 °C
Т	16 °C to 43 °C
SN-ST	10 °C to 38 °C
SN-T	10 °C to 43 °C

If your appliance does not have a fixed water connection, then the appliance is guaranteed to function correctly down to a lower ambient temperature of -15 °C.

## 1.5 Conformity

The refrigerant circuit has been tested for leaks. The appliance complies with the applicable safety regulations and with the corresponding directives.

For market	the :*	EU	The appliance complies with directive 2014/53/EU.*
For market	the :*	GΒ	The appliance complies with Radio Equipment Regulations 2017 SI 2017 No. 1206.*

The full text of the EU Declaration of Conformity is available on the following website: www.Liebherr.com

## 1.6 SVHC substances according to **REACH** regulation

You can check whether your appliance contains SVHC substances according to REACH regulation at the following link: home.liebherr.com/de/deu/de/liebherr-erleben/nachhaltigkeit/umwelt/scip/scip.html

## 1.7 EPREL database

Details about energy labelling and ecodesign requirements will be available on the European product database (EPREL) from 1st March 2021. You can access the product database at the following link: https://eprel.ec.europa.eu/ You will be asked to enter the model ID. You can find the model ID on the nameplate.

## 1.8 Spare parts

The spare parts availability for functional parts and stockable parts of the equipment is 15 years.

## 2 General safety instructions

Please keep these operating instructions in a safe place so you can refer back to them at any time.

If you pass the appliance on, please hand these operating instructions to the next user.

Read these operating instructions carefully before use to ensure safe and correct use of the appliance. Follow the instructions, safety instructions and warning messages included at all times. They are important for ensuring you can operate and install the appliance safely and without any problems.

## Danger for the user:

 This device can be used by children and people with impaired physical, sensory or mental abilities or with a lack of experience and knowledge provided that they are supervised or have received instruction in the safe use of this device, and about the resulting hazards.

Children must not play with this appliance. Cleaning and user maintenance work must not be carried out by children without adult supervision. Children aged between 3 and 8 are allowed to load and unload the appliance. Children below the age of 3 must be kept away from the appliance unless they are under continuous adult supervision.

- The socket must be easily accessible so that the appliance can be disconnected quickly from the electricity in an emergency. It must not be located in the area behind the appliance.
- When disconnecting the appliance from the supply, always take hold of the plug. Do not pull the cable.
- In the event of a fault pull out the mains plug or deactivate the fuse.
- Do not damage the mains power cable. Do not operate the appliance with a defective mains power cable.
- Only customer service or other specially trained staff may repair or perform other operations on the appliance.
- Only assemble, connect and dispose of the appliance according to the instructions.

## Fire hazard:

- The coolant used (information on the model plate) is ecofriendly but also flammable. Any leaking coolant may ignite.
  - Do not damage the refrigerant circuit pipes.
  - Do not handle ignition sources inside the appliance.
  - Do not use electrical appliances inside the appliance (e.g. steam cleaners, heaters, ice cream makers, etc.).
  - If the refrigerant leaks: remove any naked flames or ignition sources from the vicinity of the leakage point. Properly air the room. Inform customer services.
- Do not store explosives or sprays using combustible propellants such as butane, propane, pentane, etc. in the appliance. To

identify these spray cans, look for the list of contents printed on the can, or a flame symbol. Gases possibly escaping may ignite due to electrical components.

- Keep burning candles, lamps and other items with naked flames away from the appliance so that they do not set the appliance on fire.
- Please be sure to store alcoholic drinks or other packaging containing alcohol in tightly closed containers. Any alcohol that leaks out may be ignited by electrical components.

## Danger of tipping and falling:

• Do not misuse the plinth, drawers, doors etc. as a step or for support. This applies particularly to children.

## Danger of food poisoning:

- Do not consume food which has been stored too long.

## Danger of frostbite, numbness and pain:

 Avoid prolonged skin contact with cold surfaces or refrigerated/frozen goods or take protective measures, e.g wear gloves.

## Danger of injury and damage:

- Hot steam can lead to injury. Do not use electrical heating or steam cleaning equipment, open flames or defrosting sprays to defrost.
- Do not use sharp implements to remove the ice.

## **Risk of crushing:**

Do not hold the hinge when opening and closing the door. Fingers may get caught.

## Symbols on the appliance:



This symbol may be located on the compressor. It relates to the oil in the compressor and makes reference to the risk that: Swallowing or inhaling can be fatal. This advice is only relevant to recycling. There is no danger in normal operation.



This symbol is located on the compressor and indicates the danger of flammable materials. Do not remove the sticker.



This or a similar sticker may be located on the rear of the appliance. This sticker indicates that there are vacuum insulation panels (VIP) or perlite panels in the door and/or housing. This advice is only relevant to recycling. Do not remove the sticker.

Please note the warning messages and other specific advice in the other chapters:

# Functionality of the Touch display

DANGER	indicates an immediately hazardous situation which will lead to death or serious injuries if it is not avoided.
WARNING	indicates a hazardous situation which may lead to death or serious injuries if it is not avoided.
CAUTION	indicates a hazardous situation which may lead to minor or moderate injuries if it is not avoided.
NOTICE	indicates a hazardous situation which may lead to damage to property if it is not avoided.
Note	indicates useful instructions and tips.

Symbol	Description
<ul> <li>➡</li> <li>➡</li> <li>2s</li> <li>5s</li> <li>10s</li> </ul>	Arrow with a time indication: It takes the specified amount of time until the following message appears in the display.
	<b>"Open Settings menu" symbol:</b> Navigates to the Settings menu and opens the settings menu. If necessary: Navigate to the desired function in the Settings menu. (see 3.2.1 Opening the Settings menu)
	<b>"Open Advanced menu" symbol:</b> Navigates to the Advanced menu and opens the advanced menu. If necessary: Navigate to the desired function in the Advanced menu. (see 3.2.2 Opening the Advanced menu)
No action for 10 seconds	If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.
Opening door and closing it again	If you open the door and immedi- ately close it again, the display jumps directly back to the status display. <i>isplay are shown in the English</i>

Note: Illustrations of the display are shown in the English version.

## 3.2 Menus

Г

The appliance functions can be found in various menus.

Menu	Description
Main menu	When you switch the appliance on, you are automatically in the main menu.
	From here you can navigate to the most important appliance functions, to the Settings menu and to the Advanced menu.
ک Settings	The Settings menu contains additional appliance functions for setting up your appliance. (see 3.2.1 Opening the Settings menu)
Settings menu	
Advanced menu	The advanced menu contains special appli- ance functions for setting up your appli- ance. Access to the Advanced menu is protected by the numerical code <b>151</b> . (see 3.2.2 Opening the Advanced menu)

## 3.2.1 Opening the Settings menu



# **3** Functionality of the Touch display

You operate your appliance using the Touch display. You select appliance functions in the Touch display (hereafter referred to as display) by tapping them. If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.

# 3.1 Navigation and symbol explanation

In the illustrations, different symbols are used to navigate the display. The following table describes these symbols.

Symbol	Description
	Press the Next navigation arrow: Navigates to the next option in the menu.
	Press the Back navigation arrow: Jumps back one option in the menu.
	<b>Press the navigation arrow</b> <b>several times in succession:</b> Navigates in the menu to the desired function.
	<b>Press the Confirm symbol:</b> Activates/deactivates function. Opens submenu.
Back	Press the Confirm symbol together with the back icon: Jumps back one menu level.
<ul> <li>➡</li> <li>♥</li> </ul>	Arrow with clock: It takes more than 10 seconds for the following message to appear in the display.

# **Putting into operation**

Fig. 2 Example illustration

- Carry out action steps according to the illustration.
- ▶ Settings menu is open.
- If necessary: Navigate to the desired function.

## 3.2.2 Opening the Advanced menu



#### Fig. 3




Fig. 4 Example illustration, access with numerical code 151
Carry out action steps according to the illustration.

- The expanded menu is open.
- ▶ If necessary: Navigate to the desired function.

## 3.3 Sleep mode

If you do not touch the display for 1 minute, the display switches to sleep mode. In sleep mode, the display brightness is dimmed.

## 3.3.1 Ending sleep mode

- Press any navigation key.
- Sleep mode is ended.

# 4 Putting into operation


## 4.1 Switching on appliance (first use)

Make sure that the following requirements are fulfilled:

- □ The appliance has been installed and connected in accordance with the installation instructions.
- □ All adhesive strips, adhesive and protective films and transport locks are removed from inside and on the appliance.
- □ All marketing leaflets are removed from the drawers.
- □ You are familiar with the functionality of the Touch display. (see 3 Functionality of the Touch display)

## Switch on the appliance using the Touch display:

- ▶ If the display is in sleep mode: Press the confirmation symbol.
- Carry out action steps according to the illustration.



- Fig. 5 Example illustration
- ▶ Status display appears.
- > The appliance cools to the temperature set at the factory.
- The appliance starts in demo mode (status display with DEMO appears): If the appliance starts in demo mode, you can deactivate demo mode within the next 5 minutes. (see Demo mode)

#### More information:

- Start the EasyTwist-Ice for the first time. (see 4.2 Starting the EasyTwist-Ice for the first time\*) \*
- Start the SmartDevice for the first time. (see 1.3 Smart-Device) and (see WiFi)

#### Note

The manufacturer recommends:

- ▶ Store frozen foods at -18 °C or colder.
- Observe the notes on storing food. (see 5.1 Information regarding storage)

#### Note

Accessories can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/ zubehor.html.

# **4.2** Starting the EasyTwist-Ice for the first time\*

If your appliance is equipped with EasyTwist-Ice, you must clean the EasyTwist-Ice **before using it for the first time**. Make sure that the following requirements are fulfilled:

□ The appliance is properly connected.

- Clean the EasyTwist-Ice. (see 9.3.5 Cleaning the Easy-Twist-Ice\*)
- Fill the water tank. (see Filling the water tank)

## 5 Storage

## 5.1 Information regarding storage



Do not use any electrical appliances in the food area of the appliance unless recommended by the manufacturer.

Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.
Always keep air slots clear.

Observe the following specifications for storage:

- Package food properly.
- Package raw meat or fish in clean, closed containers. This will prevent meat or fish from touching or dripping onto other food.

# Saving energy

- Leave space between goods to ensure good air circulation.
- Store food according to the instructions on the packaging.
- Always observe the best-before date indicated on the packaging.

#### Note

Failure to follow these guidelines can lead to foodstuffs spoiling.

## 5.2 Freezer compartment

Here, a dry, frosty storage climate is created at -18 °C. The frosty storage climate is suitable for storing frozen food for several months, for making ice cubes or freezing fresh food.

## 5.2.1 Freezing food

#### **Freezing quantity**

The maximum amount of fresh food that you can freeze within 24 hours is specified on the type plate (see 10.5 Model plate) under "Freezing capacity ... kg/24h".

To ensure that food quickly freezes through, adhere to the following quantities per package:

- Fruit and vegetables up to 1 kg
- Meat up to 2.5 kg

#### Freezing food using SuperFrost

Depending on the quantity to be frozen, you can activate SuperFrost before freezing in order to achieve lower freezing temperatures. (see SuperFrost)

Activate SuperFrost if the amount of food you have to freeze is more than approx. 2 kg.

The time at which you activate SuperFrost depends on the amount of food you have to freeze:

Freezing quan- tity	Time at which you should activate SuperFrost
Small amount of food to freeze	Activate SuperFrost about 6 hours before freezing.
	You can place the food in the freezer as soon as the appliance automatically deactivates SuperFrost.
Maximum amount of food	Activate SuperFrost about 24 hours before freezing.
to freeze	You can place the food in the freezer as soon as the appliance automatically deactivates SuperFrost.

#### Arranging your food properly

# 

Risk of injury from broken glass!


Bottles and cans with beverages can burst during freezing. This applies in particular to carbonated beverages.

Only freeze bottles and cans with beverages if you have activated the BottleTimer function in the SmartDevice app.

Freezing quan- tity	Arranging your food properly
food to freeze	Place packaged food in the top drawer. If possible, place groceries at the back of the drawer near the rear wall.

Freezing quan- tity	Arranging your food properly
Maximum amount of food to freeze	Distribute packaged groceries throughout all drawers, but only place frozen food in the bottom drawer.
	If possible, place groceries at the back of the drawer near the rear wall.

## 5.2.2 Defrosting food



Risk of food poisoning!

- ▶ Do not re-freeze thawed food.
- ► Use defrosted foodstuff as soon as possible.

You can defrost food in several ways:

- In a fridge
- In the microwave
- In the oven/fan-assisted oven
- At room temperature
- ▶ Take out only as much food as necessary.

## 5.2.3 Freezer tray\*

You can freeze berries, herbs, vegetables and other small frozen food in the freezer tray without it all freezing together. The frozen food is less likely to get squashed and subsequent portioning is easier.

In addition, you can store the cold storage accumulators in the freezer tray to save space.\*

Distribute food on the freezer tray without packaging and well spaced out.

## 5.3 Storage times

Refer to the specified storage times as a guide.

In the case of foods with a minimum shelf life, the date indicated on the packaging still applies.

Recommended storage period for various types of food			
Ice cream	at -18 °C	2 to 6 months	
Sausages, ham	at -18 °C	2 to 3 months	
Bread, baked goods	at -18 °C	2 to 6 months	
Game, pork	at -18 °C	6 to 9 months	
Fatty fish	at -18 °C	2 to 6 months	
Lean fish	at -18 °C	6 to 8 months	
Cheese	at -18 °C	2 to 6 months	
Poultry, beef	at -18 °C	6 to 12 months	
Vegetables, fruit	at -18 °C	6 to 12 months	

## 6 Saving energy

- Pay attention to good ventilation. Do not cover ventilation holes or grids.
- Always keep the fan air slits clear.
- Do not place the appliance in direct sunlight or near radiators or similar sources of heat.
- If the appliance is placed directly next to an oven, the energy consumption may increase slightly. This is dependent on the service life and usage intensity of the oven.

- Energy consumption depends on the installation conditions, e.g. the ambient temperature (see 1.4 Appliance range of use) . A warmer ambient temperature can increase the energy consumption.
- Open the appliance for as short a time as possible.
- The lower the temperature is set the higher the energy consumption.
- Keep all food properly packed and covered. This prevents frost from forming.
- Inserting warm food: allow to cool down to room temperature first.

#### Controls 7

## 7.1 Controls and displays

## 7.1.1 Status display



Fig. 6

(1) Temperature display

The Status display shows the set temperature and is the home display. From there, you can navigate to the options and settings.

## 7.1.2 Display symbols

Display symbols provide information on the current appliance status:

Symbol	Appliance status
()	<b>Standby</b> The appliance or temperature zone is switched off.
	Flashing number
	Appliance is working. Temperature flashes until the set value is reached.
	Flashing symbol
	Appliance is working. Setting is made.



Bar grows steadily Function is activated.

## 7.2 Appliance functions

## 7.2.1 Notes on the appliance functions

The appliance functions are set at the factory so that your appliance is fully functional.

Before you alter, activate or deactivate the device functions, make sure that the following requirements are met:

- You have read and understood the descriptions of how the display works. (see 3 Functionality of the Touch display)
- □ You have familiarised yourself with the operating and display elements of your appliance.



Switching the appliance off and on

Use this function to switch the entire appliance off and on.

### Switching off the appliance


When you switch the appliance off, then the previously saved settings are saved.

Make sure that the following requirements are fulfilled:

□ Handling instructions (see 11 Shutting down) are carried out.







## Fig. 8

- Carry out action steps according to the illustration.
- Appliance is switched off.
- The standby symbol appears in the display.
- Display turns black.

#### Switching on the appliance

- If the display is in sleep mode:
- Press any navigation key.




Fig. 9 Example illustration

- Carry out action steps according to the illustration. When the appliance starts in demo mode:
- Deactivating demo mode. (see Deactivating demo mode)
- The appliance is switched on.
- ⊳ Previous settings are restored.
- The appliance cools to the target temperature set. ⊳



Use this function to connect your appliance to WiFi. You can then operate it via the SmartDevice app on a mobile device. You can also use this function to disconnect or reset the WiFi connection.

To connect your device to WiFi, you need the SmartDeviceBox.\*

More information on the SmartDevice: (see 1.3 SmartDevice)

#### Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan. You cannot use the SmartDeviceBox.\*

# Controls

## Establishing the WiFi connection for the first time

Make sure that the following requirements are fulfilled:

- □ You have purchased and inserted a SmartDeviceBox. (see 1.3 SmartDevice) \*
- □ You have installed the SmartDevice app (see apps.home.liebherr.com).
- □ Registration in the SmartDevice app is completed.








Fig. 11

- Carry out action steps according to the illustration.
- Connection is established.

## Disconnecting from the WiFi



Fig. 12





Fig. 13

Carry out action steps according to the illustration.
 There is no connection.

## Resetting the WiFi connection



Fig. 14



## Fig. 15

- Carry out action steps according to the illustration.
- WiFi connection and other WiFi settings are reset to factory settings.

## Showing information about the WiFi connection



Fig. 16




Fig. 17

• Carry out action steps according to the illustration.

#### -18° Temperature

Use this function to set the temperature.

The temperature depends on the following factors:

- Frequency of door opening
- Duration of door opening
- Room temperature of the installation site
- Type, temperature and quantity of food

	Factory-set temperature	Recommended setting
-180	-18 °C	-18 °C

#### Setting the temperature




Fig. 18 Example illustration

- Carry out action steps according to the illustration.
- Temperature is set.


## ℃∕ F Temperature unit

Use this function to set the temperature unit. You can set degrees Celsius or degrees Fahrenheit as the temperature unit.

#### Setting the temperature unit



Fig. 19



*Fig. 20 Example illustration: Switch from degrees Celsius to degrees Fahrenheit.* 

Carry out action steps according to the illustration.
 The temperature unit is set.

# 

You can use this function to activate or deactivate SuperFrost. If SuperFrost is activated, then the appliance increases the freezing capacity. It allows you to achieve lower freezing temperatures.

#### Application:

- Quickly freeze fresh food through to the core.
- This ensures that the nutrition, appearance and taste of frozen food is maintained.
- Increase the cold reserve in stored frozen food before defrosting the appliance.

If the function is active, the appliance operates at higher power. As a result, the appliance's operating noise may be temporarily louder and energy consumption will increase.

## Activating SuperFrost

Make sure that the following requirements are fulfilled:

Freezing quantity and time for activation of SuperFrost are taken into account. (see Freezing food using SuperFrost)




Fig. 21




Fig. 22

- Carry out action steps according to the illustration.
- -or-
- Activate with the SmartDevice app.\*
- SuperFrost is activated.

#### **Deactivating SuperFrost**

SuperFrost is automatically deactivated after 56 to 72 hours depending on the quantity of the food inserted. However, you can also deactivate SuperFrost manually at any time:



Fig. 23




Fig. 24

- Carry out action steps according to the illustration.
- or Deactivate with the SmartDevice app.\*
- SuperFrost is deactivated.
- The appliance continues to run in normal mode.
- The appliance cools to the temperature set previously.

# \*∕

## Start defrosting cycle

Use this function to start the automatic defrosting cycle manually if it does not start automatically in the event of a fault.

## Starting defrosting cycle



Fig. 25

# Controls




Fig. 26

- Carry out action steps according to the illustration.
- > Defrosting cycle has started: Icon flashes until defrosting cycle is automatically completed.
- ▶ When defrosting cycle is finished: The device continues to run in normal mode.

#### Cancelling defrosting cycle

The defrosting cycle will be stopped automatically. However, you can also cancel the defrosting cycle at any time during the defrosting process:




Fig. 27

- Carry out action steps according to the illustration.
- Defrosting cycle is cancelled.
- > The device continues to run in normal mode.

#### ŲŊ PartyMode

You can use this function to activate or deactivate Party-Mode. PartyMode activates various functions that are useful for a party.

PartyMode activates the following functions:

- SuperFrost (see SuperFrost)

You can adjust all listed functions individually and flexibly. When you deactivate PartyMode, all changes are discarded.

If the function is active, the device operates at higher power. As a result, the device's operating noise may be temporarily louder and energy consumption will increase.

## **Activating PartyMode**



Fig. 28




Fig. 29

- Carry out action steps according to the illustration.
- PartyMode and the associated functions are activated.
- > The current temperature flashes until the target temperature is reached.

#### **Deactivating PartyMode**

The PartyMode is automatically deactivated after 24 seconds. However, you can also deactivate PartyMode manually at any time:





Fig. 30



Fiq. 31

- Carry out action steps according to the illustration.
- ▶ PartyMode is deactivated.
- ⊳ The appliance cools to the temperature set previously: The current temperature flashes until the target temperature is reached.



# SabbathMode

You can use this function to activate or deactivate SabbathMode. If you activate this function, some electronic functions are switched off. As a result, your device meets the religious requirements for Jewish holidays such as Sabbath and complies with STAR-K Kosher certification.

Device status when SabbathMode is active

The status display shows SabbathMode permanently.

All functions on the display are locked except for the Deactivate SabbathMode function.

Active functions remain active.

The display remains bright when you close the door.

Reminders are not implemented. The set time interval stops.

Reminders and warnings are not displayed.

There is no door alarm.

There is no temperature alarm.

The defrosting cycle operates only for the specified time, without considering the appliance consumption.

After a power failure, the appliance returns to SabbathMode.

Device status

#### Note

This appliance has certification from the "Institute for Science and Halacha". (www.machonhalacha.co.il)

You can find a list of STAR-K-certified appliances at www.star-k.org/appliances.

#### Activating SabbathMode

# 

Danger of food poisoning from spoiled food!

If you have SabbathMode activated and a power failure occurs, no message appears in the status display about the power failure. Once the power is restored, the appliance continues to operate in SabbathMode. The power failure may mean that food spoils and the consumption of this food could lead to food poisoning.

After a power failure:

Do not consume food that was frozen and has thawed out.



Fig. 32




Fig. 33

- Carry out action steps according to the illustration.
- SabbathMode is activated.
- ▶ The status display shows SabbathMode permanently.

#### Deactivating SabbathMode

The SabbathMode is automatically deactivated after 80 hours. However, you can also deactivate SabbathMode manually at any time:




Fig. 34

- Carry out action steps according to the illustration.
- SabbathMode is deactivated.

## E-Saver

You can use this function to activate or deactivate Energy saving mode. If energy saving mode is activated, the energy consumption decreases and the temperature in the device increases. The food remains fresh, but the shelf life is shortened.

Temperature zone	Recommended setting (see Setting the temperature)	Temperature with active E-Saver
-18.	-18 °C	-16 °C

Temperatures

## **Activating E-Saver**




Fig. 35



Fig. 36

- Carry out action steps according to the illustration.
- Energy saving mode is activated.

#### **Deactivating E-Saver**



Fig. 37



Fig. 38

- Carry out action steps according to the illustration.
- Energy saving mode is deactivated.

# Display brightness

Use this function to set the display brightness in stages.

You can select the following brightness levels:

- 40 %
- 60 %
- 80%
- 100 % (pre-setting)

## Setting the brightness



Fig. 39




Fig. 40 Example illustration: Switch from 80 % to 60 %.
▶ Carry out action steps according to the illustration.
▶ The brightness is set.

# Controls

# Door alarm

Use this function to activate or deactivate the door alarm. The door alarm sounds if the door is open for too long. The door alarm is activated on delivery. You can set how long the door may be open before the door alarm sounds.

The following values can be set:

- 1 minute
- 2 minutes
- 3 minutes
- Off

#### Setting the door alarm



Fig. 41




Fig. 42 Example illustration: Change door alarm from 1 minute to 3 minutes.

- Carry out action steps according to the illustration.
- ▶ The door alarm is set.

## Deactivating the door alarm



Fig. 44




Fig. 45

• Carry out action steps according to the illustration.

▶ The door alarm is deactivated.

# Input lock

You can use this function to activate or deactivate the input lock. The input lock prevents the appliance being operated accidentally, e.g. by children.

## Application:

- Avoid unintentional modification of functions.

- Avoid unintentional switching off of the device.
- Avoid unintentional temperature setting.

## Activating the input lock

If you activate the input lock, you can continue to navigate in the menus but you cannot select or change other functions.



Fig. 46




Fig. 47

- Carry out action steps according to the illustration.
- Input lock is activated.

#### Deactivating the input lock



Fig. 48



Fig. 49

- Carry out action steps according to the illustration.
- Input lock is deactivated.



## Device information

Use this function to indicate the model name, index, serial number and service number of your device. You will need the device information when you contact customer service. (see 10.4 Customer Service)

This function also opens the Advanced menu. (see 3 Functionality of the Touch display)

#### Indicating the device information



Fig. 50

Fig. 51

- Carry out action steps according to the illustration.
- Display indicates device information.



## fware Software

Use this function to indicate the software version of your device.

#### Indicating the software version



Fig. 52



Fig. 53

- Carry out action steps according to the illustration.
- Display indicates software version.

# Demo mode

Demo mode is a special feature for dealers who want to demonstrate appliance features. If you activate demo mode, all refrigeration functions are deactivated.

If you switch on your appliance and "Demo" appears in the status display, then demo mode is already activated.

If you activate and then deactivate demo mode, the appliance will be reset to factory defaults. (see Resetting to factory settings)

## Activating demo mode



Fig. 54




Fig. 55

- Carry out action steps according to the illustration.
- Demo mode is activated.
- Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
- ▶ "DEMO" appears in the status display.

#### Deactivating demo mode





Fig. 56



#### Fig. 57

- Carry out action steps according to the illustration.
- ▶ Demo mode is deactivated.
- ▶ Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
- Appliance is reset to factory settings.

## Resetting to factory settings

Use this function to reset all settings to factory defaults. All settings you have made so far are reset to their original settings.

## Performing a reset







Fig. 59

# Controls

- ▶ Carry out action steps according to the illustration.
- Device is reset.
- Device is switched off.
- Restart the device. (see 4.1 Switching on appliance (first use))

## 7.3 Messages

There are two categories of messages:

Category	Importance
Warning	Warnings appear in the event of a door alarm or malfunction.
	Simple warnings can be cancelled by yourself. In the event of serious malfunctions, you must contact customer service. (see 10.4 Customer Service)
Reminder	Reminders remind you of general processes. You can carry out these operations to end the message.

## 7.3.1 Overview of warnings

Behaviour of the appliance in the event of warnings:

- Warning appears on the display.
- The alarm tone sounds at an ever-increasing volume.

Message	Cause	Exit the message
	The message appears if the door is open for too long.	Carry out action steps (see Door alarm).
Door alarm		
×	The message appears if the freezing tempera- ture has risen due to a power failure.	Carry out action steps (see Power outage alarm).
Power outage alarm		
	The message appears if the freezing temper- ature does not corre- spond to the set temperature.	
Temperature alarm		
Error	The message appears if there is an appliance error. A component of the appliance has a fault.	action steps
WiFi Error *	The message appears if the appliance could not be connected to the WLAN. (see Establishing the WiFi connection for the first time) *	Carry out action steps (see WLAN error*).*

## 7.3.2 Ending warnings

## Door alarm



Fig. 60 Example illustration

► Carry out action steps according to the illustration.

- -or-
- Close the door.

> The display returns to the status indicator.

You can set how long the door may be open before the door alarm sounds. (see Setting the door alarm)

## Power outage alarm

When the power failure has ended, the appliance cools down to the previously set target temperature.




Fig. 61 Example illustration

- Press the confirmation symbol.
- ▶ Warmest freezing temperature is displayed.
- ▶ If the freezing temperature was below -9 °C: Food can still be consumed.
- If the freezing temperature has risen above -9 °C: Check the food.
- Press the confirmation symbol.
- The display returns to the status indicator: Current temperature and target temperature are displayed.

## Temperature alarm

Temperature differences can be caused by:

- You have put in warm, fresh food.
- Too much warm air has got in while you were sorting out the freezer or removing items.
- There has been a longer power failure.
- The appliance is faulty.
- Eliminate causes.
- The appliance cools to the target temperature set previously.




Fig. 62 Example illustration

- Press the confirmation symbol.
- ▶ Warmest freezing temperature is displayed.

▶ If the freezing temperature was below -9 °C: Food can still be consumed.

If the freezing temperature has risen above -9 °C:

- Check the food.
- Press the confirmation symbol.
- The display returns to the status indicator: Current temperature and target temperature are displayed.

## Error




Fig. 63 Example illustration

- Press the confirmation symbol.
- Error code is displayed.
- ▶ Note the error code.
- Press the confirmation symbol.
- > The display returns to the status indicator.
- Contact Customer Service. (see 10.4 Customer Service)

## WLAN error\*

- Check WLAN connection.
- ▶ Reconnect the appliance to the WLAN. (see WiFi)

## 7.3.3 Overview of reminders

Behaviour of the appliance during reminders:

- Reminder appears on the display.
- Alarm tone sounds.

# 8 Features

## 8.1 Drawers

You can remove the drawers for cleaning.

You can remove the drawers to use VarioSpace.

The way to remove/insert the drawers varies depending on the pull-out system. Your appliance can contain various pull-out systems.

## Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.

- Leave the bottom drawer in the appliance!
- Always leave the fan air vents clear on the back wall!

## 8.1.1 Top tilting drawer\*

When you pull out the top drawer, it tilts forward. This gives you a better view into the drawer. The function depends on the height of the appliance.

## Removing drawer





Fig. 64

- Pull out drawer as far as it will go.
- ► Lift drawer at the front.

- Lift drawer from below.
- Remove drawer to the front.

## Inserting drawer



#### Fig. 65

- ► Guide drawer around the upper stoppers. *Fig. 65 (1)*
- Place drawer at an angle behind the lower stoppers onto moulded rib. Fig. 65 (2)
- Lower drawer.
   Slide to the back.

## 8.1.2 Drawer on moulded rib

The drawer runs directly on the moulded rib. There are no rails.

## **Removing drawer**





Fig. 66

- Pull out drawer as far as it will go.
- Lift up drawer at the front. *Fig. 66 (1)*
- Remove drawer to the front. *Fig. 66 (2)*

## Inserting drawer



#### Fig. 67

- Place drawer at an angle behind the stoppers on the moulded rib. (see Fig. 67)
- Lower drawer.
   Slide in drawer to the back.

## 8.1.3 Bottom drawer

The drawer is the lowest drawer in the appliance. It runs directly on the moulded rib. There are no rails.

## **Removing drawer**




Fig. 68

Pull out drawer as far as it will go.

# **Features**

- Lift up drawer at the front. Fig. 68 (1).
- Remove drawer to the front. *Fig. 68 (2)*.

## Inserting drawer





Fig. 69

- Guide drawer in at an angle around the stoppers Fig. 69 (1).
- Lower drawer.
- Slide in drawer to the back.

## 8.2 EasyTwist-Ice\*

With the EasyTwist-Ice you can make enough ice cubes for the whole household. The EasyTwist-Ice is supplied with water via a water tank.



- Fig. 70 Example illustration
- (4) Rotary knob (1) Freezer drawer with EasyTwist-Ice
- (2) Body with ice cube tray (5) Ice cube drawer (3) Water tank

#### Note

Do not change the position of the freezer drawer with the EasyTwist-Ice in the appliance.

## 8.2.1 Making ice cubes

The amount of ice cubes you can make in a given period of time with the EasyTwist-Ice depends on the freezer temperature of the appliance. The lower the temperature in the appliance, the more ice cubes you can make.

Maximum number of ice cubes in the ice cube tray:	20 ice cubes
Maximum capacity of the ice cube drawer:	40 ice cubes (equivalent to two ice cube batches)
More information about the time needed for ice cube production:	

Make sure that the following requirements are fulfilled: □ Components of the EasyTwist-Ice have been cleaned.

## Filling the water tank



Risk of poisoning due to contaminated water! Only fill the water tank with potable water.

## NOTICE


Sugar-content liquids! Damage to EasyTwist-Ice. Only fill with cold drinking water.

#### Note

Using filtered, decarbonised water ensures the best-tasting drinking water for your ice cubes.


This water quality can be achieved using a table water filter of the kind available in trade retail outlets.

Always fill the water tank only with filtered, decarbonised drinking water.



## Fig. 71

- Pull out freezer drawer as far as it will go.
- Lift the water tank at the recess Fig. 71 (1).
- Remove the water tank by lifting it upwards. Fig. 71 (2)
- Fill the water tank with drinking water up to the mark Fig. 71 (3).



## Fig. 72

- Position the water tank at the front. Fig. 72 (1)
- Lower the water tank at the rear. Fig. 72 (2)
- Slide in the freezer drawer.

## **Releasing the ice cubes**

Make sure that the following requirements are fulfilled:

- □ The required time for the production of ice cubes has been observed. (see 10.1 Technical specifications)
- □ Freezer drawer is fully inserted.
- □ Ice cube drawer is fully inserted.
- ▶ Turn the rotary knob Fig. 70 (4) clockwise as far as it will go.

- ▶ Ice cubes fall from the ice cube tray into the ice cube drawer *Fig. 70 (5)*.
- If all the ice cubes do not come out of the ice cube tray:
   Turn the rotary knob clockwise several times to the stop.

## 8.3 VarioSpace




Fig. 73

You can remove drawers and glass panels from your appliance. This provides more room for large food items such as poultry, joints of meat, large game, and tall baked products. You can then freeze these items whole for later preparation.

Note the weight limits on the drawers and glass panels (see 10.1 Technical specifications).

## 8.4 Freezer pack\*

Freezer packs prevent the temperature rising too quickly should there be a power cut.

The freezer packs are in the drawer.

You can store the freezer packs in the freezer tray.\*

## 8.4.1 Using the freezer pack




Fig. 74

When the freezer packs are fully frozen:

Place on the frozen goods in the top, front part of the freezer.

## 9 Maintenance

## 9.1 Disassembling / assembling pullout systems

## 9.1.1 Notes on disassembly

You can disassemble some of the pull-out systems for cleaning. Your appliance can contain a variety of pull-out systems.

The following pull-out systems can be disassembled or cannot be disassembled:

Pull-out system	can be disassembled / cannot be disassembled	
Top tiltable drawer*	cannot be disassembled*	
Drawer guided on container rib	can be disassembled (see 9.1.2 Drawer on moulded rib)	
Bottom drawer	cannot be disassembled	

## 9.1.2 Drawer on moulded rib

### Disassembling pull-out system

Make sure the following prerequisites are met:

Drawer has been removed. (see 8.1.2 Drawer on moulded rib)




Fig. 75 Attachment on the right moulded rib

- Grab attachment at the back from below.
- Pull off attachment at the back sideways. Fig. 75 (1)
- Pull off attachment at the front sideways. Fig. 75 (2)

#### Installing pull-out system




Fig. 76 Attachment on the right moulded rib

- Position attachment on moulded rib at the front. Fig. 76 (1)
- Press on attachment at the back. Fig. 76 (2)

## 9.2 Defrosting the appliance

## 9.2.1 Defrosting with NoFrost

Defrosting is performed automatically with the NoFrost system. The moisture is deposited on the evaporator, is periodically defrosted and evaporates.

The appliance does not have to be defrosted.

#### Note

Water droplets may collect on the bottom of the appliance. When you take the appliance out of operation:

Place a towel in front of the appliance to catch any water droplets that escape. (see 11 Shutting down)

## 9.3 Cleaning the appliance

## 9.3.1 Ready



Danger of electric shock!

Remove the refrigerator connector or interrupt the power supply.

# 

Risk of fire

Do not damage the refrigeration circuit.

- Empty the appliance.
- Remove mains connector.

## 9.3.2 Clean the housing

#### NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

# 

Risk of injury and damage as a result of hot steam! Hot steam can lead to burns and can damage the surfaces.

- Do not use any steam cleaners!
- ▶ Wipe the housing down with soft, clean cloth. If very dirty, use lukewarm water with a neutral cleaner. Glass surfaces can also be cleaned with glass cleaner.

## 9.3.3 Cleaning the interior

#### NOTICE

Improper cleaning!

- Damage to the appliance.
- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.
- Plastic surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Metal surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.

## 9.3.4 Clean the components

#### NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

# Clean with a soft, clean cloth, lukewarm water and some detergent:

- Shelf
- · Drawer
- Freezer tray\*
- Components of the EasyTwist-Ice\*

#### Wash in the dishwasher up to 60 °C:

- Ice cube tray\*
- To disassemble components: see the relevant section.
- Clean the components.

## 9.3.5 Cleaning the EasyTwist-Ice\*

Clean the EasyTwist-Ice in the following situations:


- First use
- Not using for more than 48 hours
- When cleaning is required

#### Dismantling the EasyTwist-Ice

Make sure that the following requirements are fulfilled:

□ The drawer has been removed. (see 8.1 Drawers)

□ The drawer is placed on a table.



## Fig. 77

- Removing the water tank: Lift the water tank by the recess Fig. 77 (1).
- Remove the water tank *Fig.* 77 (2) upwards.
- Remove the ice cube drawer *Fig.* 77 (3) to the front.




Fig. 78

- Removing the EasyTwist-Ice body: Use your finger to push the tab Fig. 78 (4) down and use your other hand to lift the EasyTwist-Ice body Fig. 78 (5) from behind at the same time.
- ▶ Remove the EasyTwist-Ice body from the freezer drawer.





Fig. 79

- ▶ Removing the EasyTwist-Ice body cover: Push the tabs *Fig. 79 (6)* on both sides of the EasyTwist-Ice body with one hand.
- ▶ Use the other hand to remove the cover Fig. 79 (7) upwards.

▶ EasyTwist-Ice is dismantled into four parts. (see Fig. 80)



#### Fig. 80 Components of the EasyTwist-Ice

- (1) EasyTwist-Ice body (3) Cover
- with ice cube tray (2) Water tank
  - (4) Ice cube drawer

#### NOTICE

Risk of damage due to improper dismantling!

Equipment breaking, jumping and cracking. If you dismantle the EasyTwist-Ice body further, you may damage the rotary knob or other parts of the EasyTwist-Ice body.

- Only dismantle the EasyTwist-Ice into the components shown. (see Fig. 80)
- Clean the EasyTwist-Ice body *Fig. 80 (1)* as a whole.

#### Cleaning the EasyTwist-Ice

Make sure that the following requirements are fulfilled:

- □ The EasyTwist-Ice is dismantled. (see Dismantling the EasyTwist-Ice)
- Clean the ice cube drawer, water tank, cover and Easy-Twist-Ice body with warm water and a little detergent.
- Dry all cleaned components thoroughly with a dry cloth.
- The EasyTwist-Ice is clean.

## Installing the EasyTwist-Ice






Fig. 81

- Installing the EasyTwist-Ice body cover: Place the cover on the front. Fig. 81 (1)
- Lower the cover at the rear. *Fig. 81 (2)*
- ▶ The cover locks into both tabs *Fig. 81 (3)* audibly.



#### Fig. 82

- ▶ Installing the EasyTwist-Ice body: Push the axes for the EasyTwist-Ice body into the guides *Fig. 82* (4).
- Press the EasyTwist-Ice body *Fig. 82 (5)* down at the back.
- The EasyTwist-Ice body locks in audibly.



#### Fig. 83

▶ Insert the ice cube drawer Fig. 83 (6).

# 

Risk of poisoning due to contaminated water!
 Only fill the water tank with potable water.

- Fill the water tank with water.
- Insert the water tank.
- Insert the drawer. (see 8.1 Drawers)
- If you are using unfiltered water:
- Dispose of ice cubes that were produced 24 hours after initial ice cube production.

-or-

- If you are using filtered water:
- Dispose of ice cubes that were produced 48 hours after initial ice cube production.

## 9.3.6 After cleaning

- ▶ Wipe the appliance and the components dry.
- Connect and switch on the appliance.
- Activate SuperFrost (see 7.2 Appliance functions) .
- The temperature is cold enough:
- Place the food inside.

# Customer help

► Repeat cleaning regularly.

# 10 Customer help

## 10.1 Technical specifications

Temperature range			
Freeze -28 °C	-28 °C to -15 °C		
Maximum ice cube c	uantity / 24	hours	
Freezer compart- see type plate under "Freezing ment capacity/ 24 h"			
Maximum loading w	eight for the	equipment	
Equipment	Appliance width 600 mm (see installa- tion instruc- tions, device dimen- sions)	Appliance width 700 mm (see instal- lation instruc- tions, device dimen- sions)	Appliance width 750 mm (see installa- tion instruc- tions, device dimen- sions)
Drawer on container rib (see 8.1.2 Drawer on moulded rib)	19 kg	25 kg	
Bottom drawer (see 8.1.3 Bottom drawer)	ll kg	19 kg	
Top tiltable drawer* (see 8.1.1 Top tilting drawer*) *	19 kg*	19 kg*	*

Ice cube production with EasyTwist-Ice*		
Time required at -18 °C approx. 5.5 hours		
Time required with SuperFrost activated	approx. 3 hours	

For appliances with a WiFi connection:\*

Frequency specification*		
Frequency band	2.4 GHz	
Maximum radiated power	< 100 mW	
	Integration in the local WiFi network for data communication	

## 10.2 Operating noises

The appliance makes different noises when it is on.

- At higher temperatures the appliance uses less energy but works for longer. It is quieter.
- At lower temperatures the food is cooled faster. It is louder.

Examples:

- Functions on (see 7.2 Appliance functions)
- Fan running
- Food recently added
- High ambient temperature
- Door open for a while

Noise	9		Possible cause		e of noise
Bubbling splashing	and	Coolant into the circuit.	flowing cooling	Nori nois	mal operating se
Hissing		Coolant into the circuit.	sprays cooling	Norr nois	
Humming		The is cooli volume on the output.	appliance ng. The depends cooling	Nori nois	
Humming rustling	and	The fan is	running.	Nori nois	
Clicking		Compone switched off.	nts are on and	Nori nois	mal switching se
Rattling humming	or	Valves or working.	flaps are	Nori nois	mal switching se
Faint knoc humming buzzing*	king, or	The valve	is active.	Norr nois	
Noise	Pos: cau	sible se	Type of no	oise	Lifting
Vibration	Imp setu	roper Ip	Defective noise		Level the appliance using the adjustable feet.
Rattling	Components		Defective		Secure

## 10.3 Technical fault

Your appliance is designed and built to ensure it works reliably and has a long service life. In the unlikely event that a fault occurs during operation, please check whether it is due to an operating error. If so, you will be charged for the callout and repair costs even if it falls within the warranty period.

noise

You can fix the following faults yourself.

items inside the appliance

## 10.3.1 Appliance function

Defect	Cause	Remedy	
	$\rightarrow$ The appliance is not switched on.	<ul> <li>Switch the appliance on.</li> </ul>	

components.

Leave enough

space between the items.

Defect	Cause	Remedy
The appliance is not working.	→ The power plug is not properly plugged into the socket.	<ul> <li>Check the power plug.</li> </ul>
	→ There is something wrong with the power outlet fuse.	<ul> <li>Check the fuse.</li> </ul>
	→ Power cut	<ul> <li>Keep the appliance closed.</li> <li>Safeguarding food: Place cold packs on top of food or use another freezer if the power cut lasts longer.</li> <li>Do not re-freeze defrosted food,</li> </ul>
	→ The IEC socket is not plugged into the appliance correctly.	<ul> <li>Check the IEC socket.</li> </ul>
Temperature is not cold enough.	→ The appliance door is not closed properly.	<ul> <li>Close the appliance door.</li> </ul>
	→ The ambient temperature is too high.	<ul> <li>Problem solution: (see 1.4 Appliance range of use)</li> </ul>
	→ The appliance was opened too many times or for too long.	<ul> <li>Wait to see if the required temperature corrects itself. If not, contact Customer Service. (see 10.4 Customer Service)</li> </ul>
	→ Too much fresh food was placed inside without SuperFrost.	<ul> <li>Solution: (see SuperFrost)</li> </ul>
	ightarrow The temperature is set incorrectly.	► Turn down the temperature and check after 24 hours.
	→ The appliance is too close to a heat source (oven, radiator, etc).	Move the appliance or the heat source.
The door seal is defective or needs to be replaced for another reason.	→ The door seal can be replaced. It can be replaced without the need for special tools.	<ul> <li>Contact Customer Service. (see 10.4 Customer Service)</li> </ul>
The appliance builds up too much ice or condensa- tion.	→ The door seal may have slipped out of its groove.	<ul> <li>Check that the door seal is well fitted in the groove.</li> </ul>
The exterior surfaces of the appliance are warm.*	→ The heat of the refrigeration circuit is used to avoid condensation.	<ul> <li>This is normal.</li> </ul>

## **10.4 Customer Service**

First check whether you can rectify the fault yourself (see 10 Customer help) . If you cannot rectify the problem, contact Customer Service.

You can find the address in the enclosed brochure "Liebherr-Service" or at home.liebherr.com/service.



Unprofessional repair! Injuries.

- Have any repairs and action not expressly specified on the appliance and mains cable carried out by service personnel only. (see 9 Maintenance)
- ► A damaged mains cable may only be replaced by the manufacturer, the manufacturer's Customer Service or a similarly qualified person.
- ▶ In the case of appliances with an IEC connector, the change may be made by the customer.

## 10.4.1 Contacting Customer Service

Make sure that the following appliance information is available:

Appliance name (model and index)

- Service no. (Service)
- Serial no. (S no.)
- Call up the appliance information via the display. (see Device information)
   -or-
- Refer to the type plate for appliance information. (see 10.5 Model plate)
- ▶ Note down the appliance information.
- Notify customer service: Report errors and the appliance information.
- ▶ This will help us to provide you with a faster, more accurate service.
- ► Follow further instructions from Customer Service.

## 10.5 Model plate

The model plate is behind the drawers on the inside of the appliance.

# Shutting down




Fig. 84

(1) Appliance description
 (3) Serial no.
 (2) Service no.

▶ Note the data on the model plate.

# 11 Shutting down

- Empty the appliance.
- Switch off appliance. (see Switching the appliance off and on)
- Pull the mains plug out of the socket.
- Remove the IEC socket if required: Pull the IEC socket out of the appliance plug and move it to the left and right at the same time.
- Place a towel in front of the appliance to catch any drops of water that may run out.
- Clean appliance. (see 9.3 Cleaning the appliance)
- ▶ Leave the door open, so that no unpleasant odours arise.

# 12 Disposal

## 12.1 Preparing appliance for disposal



Liebherr uses batteries in some of its appliances. In the EU, for environmental reasons, legislation obliges the end user to remove these batteries before disposing of old appliances. If your appliance contains batteries, a corresponding notice is attached.

Lamps If you can remove the lamps yourself without destroying them, also remove these before disposal.

► Take the appliance out of operation.

▶ If possible: remove lamps without destroying them.

# 12.2 Disposing of the appliance in an environmentally friendly manner



The appliance still contains valuable materials and must be disposed of separately from unsorted municipal waste.

Dispose of batteries separately from the old appliance. To do



Lamps

this, you can return the batteries free of charge to retailers as well as recycling centres and collection centres for recyclable materials.

Dispose of removed lamps via the respective collection systems.

For Germany:

You can dispose of the appliance free of charge via the class 1 collection containers at the local recycling and recyclable material collection centres. When purchasing a new fridge/freezer, if the sales area > 400 m<sup>2</sup>, retailers will also take back the old appliance free of charge.



#### Leaking coolant and oil!

Fire. The coolant contained in the appliance is eco-friendly, but also flammable. The oil contained in the appliance is flammable. Escaping coolant and oil can ignite if the concentration is high enough and in contact with an external heat source.

- ► Do not damage the pipelines of the coolant circuit and the compressor.
- ▶ Observe the notes on transporting the appliance.
- ▶ Transport the appliance without damaging it.
- Dispose of batteries, lamps and the appliance according to the above specifications.




home.liebherr.com/fridge-manuals



Issue date: 20250507

Part number index: 7088531-00

Liebherr-Hausgeräte GmbH Memminger Straße 77-79 88416 Ochsenhausen Deutschland



# LIEBHERR

# Contents

<b>1</b> 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8	Appliance at a glance Scope of delivery Overview of the appliance and equipment SmartDevice Appliance range of use Conformity SVHC substances according to REACH regulation. EPREL database Spare parts	<b>3</b> 3 3 3 4 4 4 4 4 4 4 4
2	General safety instructions	4
<b>3</b> 3.1 3.2 3.3	Functionality of the Touch display Navigation and symbol explanation Menus Sleep mode	<b>6</b> 6 7
<b>4</b> 4.1	<b>Putting into operation</b> Switching on appliance (first use)	<b>7</b> 7
<b>5</b> 5.1 5.2 5.3 5.4	Storage Information regarding storage Fridge compartment EasyFresh Storage times	<b>7</b> 7 8 8 8
6	Saving energy	8
<b>7</b> 7.1 7.1.1 7.1.2 7.2 7.2.1	Controls Controls and displays Status display Display symbols Appliance functions Notes on the appliance functions Switching the appliance off and on	8 8 8
•))	WiFi	9
• 5 °c	Temperature	10
℃∕ℯ₣	Temperature unit	10
$\ast$	SuperCool	10
$(\mathcal{L})$	PowerCool	11
Ŵ	PartyMode *	11
$\widehat{\mathcal{T}}$	HolidayMode	12
$\mathbb{Y}$	SabbathMode	12
$\bigcirc$	E-Saver	13
$\langle O \rangle$	CleaningMode	
~) /- -/ /-	Display brightness	
K	Door alarm	
×ſm	Input lock	
Service No: Model	Device information	15

utsa: maxxxxx Hesa: xxxmaxxx Software	Software	. 15
$\Sigma$	Reminder	. 15
$\bigcirc$	Demo mode	. 15
( <b>5</b>	Resetting to factory settings	.16
7.3 7.3.1 7.3.2 7.3.3 7.3.4	Messages Overview of warnings Ending warnings Overview of reminders Ending reminders.	17 17
<b>8</b> 8.1 8.2 8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10	Features.         Door rack.         Shelves.         Dividing shelf*.         VarioSafe *.         Drawers.         Compartment lid for EasyFresh Safe.         Pull-out board with bottle basket*.         Glass shelves*.         Bottle holder.         FlexCube*.	<b>17</b> 17 18 19 21 22 23 23 24 24
<b>9</b> 9.1 9.2 9.3 9.4 9.5	Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Compartment lid for EasyFresh Safe Defrosting the appliance Cleaning the appliance	<b>24</b> 25 25 26 26
<b>10</b> 10.1 10.2 10.3 10.4 10.5	Customer help Technical specifications Operating noises Technical fault Customer Service Model plate	<b>27</b> 27 27 27 28 29
11	Shutting down	29
<b>12</b> 12.1 12.2	<b>Disposal</b> Preparing appliance for disposal Disposing of the appliance in an environmentally friendly manner	<b>29</b> 29 29

The manufacturer is continually working on the further development of all types and models. Please be aware that we reserve the right to make changes to the shape, equipment and technology.

Symbol	Explanation
	<b>Read instructions</b> Please read the information in these instruc- tions carefully to understand all of the benefits of your new appliance.

Symbol	Explanation	
	Additional information on the Internet The digital manual with additional informa- tion and in other languages can be found via the QR code on the front of the manual or by entering the service number at home.liebherr.com/fridge-manuals. The service number can be found on the serial tag:	
	Fig. Example illustration	
	<b>Check appliance</b> Check all parts for transport damage. If you have any complaints, please contact your agent or customer service.	
*	<b>Differences</b> These instructions apply to a range of models, so differences are possible. Sections that apply to certain models only are marked with an asterisk (*).	
$\land$	Instructions and results Instructions are marked with a ▶. Results are marked with a ▷.	
	<b>Videos</b> Videos about the appliances are available on the YouTube channels of Liebherr-Hausgeräte.	

#### Open source licences:

The appliance contains software components that use open source licences. Information on the open source licences used can be found here: **home.liebherr.com/** open-source-licences

These operating instructions apply to:

R / RD	42 / 46 / 50 / 52
К	46 / 52
SR	52

## 1 Appliance at a glance

## 1.1 Scope of delivery

Check all parts for transport damage. Contact your dealer or customer service in the event of complaints. (see 10.4 Customer Service)

Your new appliance comes with the following parts:

- Standalone appliance
- Features (depending on the model)
- Installation materials (depending on the model)
- "Quick Start Guide"
- "Installation Guide"
- Service Brochure

# **1.2** Overview of the appliance and equipment




Fig. 1 Example illustration

## Temperature range

- (A) Fridge section
- (B) Coldest area

#### Equipment (8) EasyFresh Safe

(9) Drain opening

(11) Vegetable drawer\*

(10) Type plate

(12) Door rack

(13) Bottle holder

- (1) Controls
- (2) Fan with FreshAir acti-
- vated charcoal filter
- (3) Divisible shelf\*
- (4) Shelf
- (5) VarioSafe\*
- (6) Bottle rack\*
- (7) Compartment lid for
  - EasyFresh Safe

## Note

Shelves, drawers and baskets are arranged for optimum energy efficiency when the appliance is delivered. Changing how the shelves, for example, are inserted in the fridge compartment does not have any impact on energy consumption.

## 1.3 SmartDevice

SmartDevice is the networking solution for your refrigerator.

If your appliance SmartDevice-enabled or compatible, you can quickly and easily connect your appliance to your WiFi. With the SmartDevice app, you can operate your appliance from a mobile device. Additional functions and setting options are available in the SmartDevice SmartDevice app.

# **General safety instructions**

SmartDeviceance:

Your appliance is compatible for use compatible appli- with the SmartDeviceBox. You must first purchase and install the Smart-DeviceBox. In order to connect your appliance to the WiFi, you need to download the SmartDevice app.



information smartdevice.liebherr.com More about SmartDevice:

Purchasing SmartDeviceBox in the Liebherr-Hausgeräte store:

the home.liebherr.com/shop/de/deu/ smartdevicebox.html

Downloading the SmartDevice app:



After installing and configuring the SmartDevice, you can connect your appliance to the WiFi using the SmartDevice app and the WiFi appliance function (see WiFi).

## Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan.

You cannot use the SmartDeviceBox.

## 1.4 Appliance range of use

## Intended use

The appliance is only suitable for cooling food products in a domestic or household-like environment. This includes, for example, use:

- in staff kitchens, bed and breakfast establishments.
- by guests in country houses, hotels, motels and other accommodation,
- for catering and similar services in the wholesale trade.

The appliance is not suitable for freezing food;

The appliance is not suitable as a built-in unit.

All other types of use are not permitted.

## Foreseeable misuse

The following applications are expressly forbidden:

- Storing and refrigerating medicines, blood plasma, laboratory preparations or similar substances and products based on the Medical Device Directive 2007/47/EC
- Use in areas at risk of explosions

Misusing the appliance may lead to damage to the goods stored or they may spoil.

## **Climate classifications**

Depending on the climate classification the appliance is designed to operate in restricted ambient temperatures. The climate classification applying to your appliance is printed on the rating plate.

#### Note

Keep to the specified ambient temperatures in order to guarantee that the appliance works properly.

Climate clas- sification	for ambient temperatures of
SN	10 °C to 32 °C
N	16 °C to 32 °C
ST	16 °C to 38 °C
Т	16 °C to 43 °C
SN-ST	10 °C to 38 °C
SN-T	10 °C to 43 °C

## 1.5 Conformity

The refrigerant circuit has been tested for leaks. The appliance complies with the applicable safety regulations and with the corresponding directives.

The full text of the EU Declaration of Conformity is available on the following website: www.Liebherr.com

## 1.6 SVHC substances according to **REACH** regulation

You can check whether your appliance contains SVHC substances according to RÉACH regulation at the following link: home.liebherr.com/de/deu/de/liebherr-erleben/nachhaltigkeit/umwelt/scip/scip.html

## 1.7 EPREL database

Details about energy labelling and ecodesign requirements will be available on the European product database (EPREL) from 1st March 2021. You can access the product database at the following link: https://eprel.ec.europa.eu/ You will be asked to enter the model ID. You can find the model ID on the nameplate.

## **1.8 Spare parts**

The spare parts availability for functional parts and stockable parts of the equipment is 15 years.

## 2 General safety instructions

Please keep these operating instructions in a safe place so you can refer back to them at any time.

If you pass the appliance on, please hand these operating instructions to the next user.

Read these operating instructions carefully before use to ensure safe and correct use of the appliance. Follow the instructions, safety instructions and warning messages included at all times. They are important for ensuring you can operate and install the appliance safely and without any problems.

## Danger for the user:

 This device can be used by children and people with impaired physical, sensory or mental abilities or with a lack of experience and knowledge provided that they are supervised or have received instruction in the safe use of this device, and about the resulting hazards.

Children must not play with this appliance. Cleaning and user maintenance work must not be carried out by children without adult supervision. Children aged between 3 and 8 are allowed to load and unload the appliance. Children below the age of 3 must be kept away from the appliance unless they are under continuous adult supervision.

- The socket must be easily accessible so that the appliance can be disconnected quickly from the electricity in an emergency. It must not be located in the area behind the appliance.
- When disconnecting the appliance from the supply, always take hold of the plug. Do not pull the cable.
- In the event of a fault pull out the mains plug or deactivate the fuse.
- Do not damage the mains power cable. Do not operate the appliance with a defective mains power cable.
- Only customer service or other specially trained staff may repair or perform other operations on the appliance.
- Only assemble, connect and dispose of the appliance according to the instructions.

## Fire hazard:

- The coolant used (information on the model plate) is ecofriendly but also flammable. Any leaking coolant may ignite.
  - Do not damage the refrigerant circuit pipes.
  - Do not handle ignition sources inside the appliance.
  - Do not use electrical appliances inside the appliance (e.g. steam cleaners, heaters, ice cream makers, etc.).
  - If the refrigerant leaks: remove any naked flames or ignition sources from the

vicinity of the leakage point. Properly air the room. Inform customer services.

- Do not store explosives or sprays using combustible propellants such as butane, propane, pentane, etc. in the appliance. To identify these spray cans, look for the list of contents printed on the can, or a flame symbol. Gases possibly escaping may ignite due to electrical components.
- Keep burning candles, lamps and other items with naked flames away from the appliance so that they do not set the appliance on fire.
- Please be sure to store alcoholic drinks or other packaging containing alcohol in tightly closed containers. Any alcohol that leaks out may be ignited by electrical components.

## Danger of tipping and falling:

- Do not misuse the plinth, drawers, doors etc. as a step or for support. This applies particularly to children.

## Danger of food poisoning:

- Do not consume food which has been stored too long.

## Danger of frostbite, numbness and pain:

 Avoid prolonged skin contact with cold surfaces or refrigerated/frozen goods or take protective measures, e.g wear gloves.

## Danger of injury and damage:

- Hot steam can lead to injury. Do not use electrical heating or steam cleaning equipment, open flames or defrosting sprays to defrost.
- Do not use sharp implements to remove the ice.

## **Risk of crushing:**

- Do not hold the hinge when opening and closing the door. Fingers may get caught.

## Symbols on the appliance:



This symbol may be located on the compressor. It relates to the oil in the compressor and makes reference to the risk that: Swallowing or inhaling can be fatal. This advice is only relevant to recycling. There is no danger in normal operation.



This symbol is located on the compressor and indicates the danger of flammable materials. Do not remove the sticker.

# Functionality of the Touch display



This or a similar sticker may be located on the rear of the appliance. This sticker indicates that there are vacuum insulation panels (VIP) or perlite panels in the door and/or housing. This advice is only relevant to recycling. Do not remove the sticker.

Please note the warning messages and other specific advice in the other chapters:

DANGER	indicates an immediately hazardous situation which will lead to death or serious injuries if it is not avoided.
WARNING	indicates a hazardous situation which may lead to death or serious injuries if it is not avoided.
CAUTION	indicates a hazardous situation which may lead to minor or moderate injuries if it is not avoided.
NOTICE	indicates a hazardous situation which may lead to damage to property if it is not avoided.
Note	indicates useful instructions and tips.

# **3** Functionality of the Touch display

You operate your appliance using the Touch display. You select appliance functions in the Touch display (hereafter referred to as display) by tapping them. If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.

## 3.1 Navigation and symbol explanation

In the illustrations, different symbols are used to navigate the display. The following table describes these symbols.

Symbol	Description		
	Press the Next navigation arrow:		
5	Navigates to the next option in the menu.		
	Press the Back navigation arrow:		
	Jumps back one option in the menu.		
	Press the navigation arrow several times in succession:		
	Navigates in the menu to the desired function.		
	Press the Confirm symbol:		
	Activates/deactivates function.		
$\bigcirc$	Opens submenu.		

Symbol		Description	
Back		Press the Confirm symbol together with the back icon: Jumps back one menu level.	
•		Arrow with clock:	
$_{\odot}$		It takes more than 10 seconds for the following message to appear in the display.	
<b>•</b> • •		Arrow with a time indication:	
2s 5s 10s		It takes the specified amount of time until the following message appears in the display.	
		"Open Settings menu" symbol:	
={\circ}}		Navigates to the Settings menu and opens the settings menu. If necessary: Navigate to the desired function in the Settings menu.	
		(see 3.2.1 Opening the Settings menu)	
		"Open Advanced menu" symbol:	
		Navigates to the Advanced menu and opens the advanced menu.	
		If necessary: Navigate to the desired function in the Advanced menu.	
		(see 3.2.2 Opening the Advanced menu)	
No action 10 seconds	for	If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.	
Opening door a closing it again	and	If you open the door and immedi- ately close it again, the display jumps directly back to the status display.	

Note: Illustrations of the display are shown in the English version.

## 3.2 Menus

The appliance functions can be found in various menus.

Menu	Description	
Main menu	When you switch the appliance on, you are automatically in the main menu.	
	From here you can navigate to the most important appliance functions, to the Settings menu and to the Advanced menu.	
ţ	The Settings menu contains additional appliance functions for setting up your appliance.	
Settings	(see 3.2.1 Opening the Settings menu)	
Settings menu		

Menu	Description
Advanced menu	The advanced menu contains special appli- ance functions for setting up your appli- ance. Access to the Advanced menu is protected by the numerical code <b>151</b> . (see 3.2.2 Opening the Advanced menu)

## 3.2.1 Opening the Settings menu




Fig. 2 Example illustration

- Carry out action steps according to the illustration.
- Settings menu is open.
- ▶ If necessary: Navigate to the desired function.

## 3.2.2 Opening the Advanced menu



#### Fig. 3




Fig. 4 Example illustration, access with numerical code 151 Carry out action steps according to the illustration. ►

- ⊳ The expanded menu is open.
- ▶ If necessary: Navigate to the desired function.

## 3.3 Sleep mode

If you do not touch the display for 1 minute, the display switches to sleep mode. In sleep mode, the display brightness is dimmed.

## 3.3.1 Ending sleep mode

- Press any navigation key.
- Sleep mode is ended.

## 4 Putting into operation


## 4.1 Switching on appliance (first use)

Make sure that the following requirements are fulfilled:

- The appliance has been installed and connected in accordance with the installation instructions.
- □ All adhesive strips, adhesive and protective films and transport locks are removed from inside and on the appliance.
- □ All marketing leaflets are removed from the drawers.
- □ You are familiar with the functionality of the Touch display. (see 3 Functionality of the Touch display)

#### Switch on the appliance using the Touch display:

- If the display is in sleep mode: Press the confirmation symbol.
- Carry out action steps according to the illustration. ►



#### Fig. 5 Example illustration

- Status display appears.
- The appliance cools to the temperature set at the factory. ⊳ ⊳ The appliance starts in demo mode (status display with DEMO appears): If the appliance starts in demo mode, you can deactivate demo mode within the next 5 minutes. (see Demo mode)

#### More information:

Start the SmartDevice for the first time. (see 1.3 Smart-Device) and (see WiFi)

#### Note

The manufacturer recommends:


- ► Stock with food: Wait for around 6 hours until the set temperature is reached.
- Observe the notes on storing food. (see 5.1 Information regarding storage)

#### Note

Accessories can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/ zubehor.html.

# 5 Storage

## 5.1 Information regarding storage



Risk of fire

Do not use any electrical appliances in the food area of the appliance unless recommended by the manufacturer.

#### Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient. Always keep air slots clear.

Observe the following specifications for storage:

- Keep the air vents on the fan free.
- Package or cover foods that readily take on or give off odours or taste in closed containers.
- Package raw meat or fish in clean, closed containers. This will prevent meat or fish from touching or dripping onto other food.
- Keep liquids in closed containers.
- Leave space between goods to ensure good air circulation.
- Store food according to the instructions on the packaging.
- Always observe the best-before date indicated on the packaging.

#### Note

Failure to follow these guidelines can lead to foodstuffs spoiling.

## 5.2 Fridge compartment

The air circulation in the appliance creates different temperature zones. You will find the different temperature zones in the appliance and equipment overview. (see 1.2 Overview of the appliance and equipment)

## 5.2.1 Arranging your food properly

- Upper area and door: Store butter, cheese, tinned food and tubes.
- Coldest temperature zone: Store perishable foods such as pre-cooked meals, meat and lunch meats.
- Bottom shelf: Store raw meat or fish.

# 5.3 EasyFresh 🖒 🖉 🔘

EasyFresh is great for non-packaged foods, such as fruit and vegetables.

The humidity in the compartment depends on the moisture content of the chilled goods placed in it, and also depends on how often the compartment is opened. You can regulate the humidity level.

## 5.3.1 Arranging your food properly

- Store unpackaged fruit and vegetables.
- If the humidity is too high: Regulate the humidity.

## 5.4 Storage times

Refer to the specified storage times as a guide.

In the case of foods with a minimum shelf life, the date indicated on the packaging still applies.

## 5.4.1 Fridge section

Always follow the best-before date stated on the packaging.

# 6 Saving energy

- Pay attention to good ventilation. Do not cover ventilation holes or grids.
- Always keep the fan air slits clear.
- Do not place the appliance in direct sunlight or near radiators or similar sources of heat.
- If the appliance is placed directly next to an oven, the energy consumption may increase slightly. This is dependent on the service life and usage intensity of the oven.

- Energy consumption depends on the installation conditions, e.g. the ambient temperature (see 1.4 Appliance range of use) . A warmer ambient temperature can increase the energy consumption.
  - Open the appliance for as short a time as possible.
- The lower the temperature is set the higher the energy consumption.
- Sort your food: home.liebherr.com/food.
- Keep all food properly packed and covered. This prevents frost from forming.
- Only take food out for as long as necessary so that it doesn't warm up too much.
- Inserting warm food: allow to cool down to room temperature first.
- For longer periods of absence, use HolidayMode (see HolidayMode).

## 7 Controls

## 7.1 Controls and displays

## 7.1.1 Status display



Fig. 6

(1) Temperature display of the fridge section

The Status display shows the set temperature and is the home display. From there, you can navigate to the options and settings.

## 7.1.2 Display symbols

Display symbols provide information on the current appliance status:

Symbol Appliance status



## Standby

The appliance or temperature zone is switched off.



#### Flashing number

Appliance is working. Temperature flashes until the set value is reached.



Flashing symbol

Appliance is working. Setting is made.



Function is activated.

## 7.2 Appliance functions

## 7.2.1 Notes on the appliance functions

The appliance functions are set at the factory so that your appliance is fully functional.

Before you alter, activate or deactivate the device functions, make sure that the following requirements are met:

- You have read and understood the descriptions of how the display works. (see 3 Functionality of the Touch display)
- You have familiarised yourself with the operating and display elements of your appliance.

## Switching the appliance off and on

Use this function to switch the entire appliance off and on.

#### Switching off the appliance

When you switch the appliance off, then the previously saved settings are saved.

Make sure that the following requirements are fulfilled:

□ Handling instructions (see 11 Shutting down) are carried out.



Fig. 7



Fig. 8

- Carry out action steps according to the illustration.
- Appliance is switched off.
- > The standby symbol appears in the display.
- Display turns black.

## Switching on the appliance

- If the display is in sleep mode:
- Press any navigation key.




Fig. 9 Example illustration

- Carry out action steps according to the illustration. When the appliance starts in demo mode:
- Deactivating demo mode. (see Deactivating demo mode)
- ▶ The appliance is switched on.
- ▶ Previous settings are restored.
- The appliance cools to the target temperature set.

# **a** WiFi

Use this function to connect your appliance to WiFi. You can then operate it via the SmartDevice app on a mobile device. You can also use this function to disconnect or reset the WiFi connection.

To connect your device to WiFi, you need the SmartDeviceBox.

More information on the SmartDevice: (see 1.3 SmartDevice)

#### Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan.

You cannot use the SmartDeviceBox.

#### Establishing the WiFi connection for the first time

Make sure that the following requirements are fulfilled:

- □ You have purchased and inserted a SmartDeviceBox. (see 1.3 SmartDevice)
- □ You have installed the SmartDevice app (see apps.home.liebherr.com).
- **D** Registration in the SmartDevice app is completed.



Fig. 10




Fig. 11

- Carry out action steps according to the illustration.
   Connection is established.





Fig. 12



#### Fig. 13

- Carry out action steps according to the illustration.
   There is no connection.
- Resetting the WiFi connection



Fig. 14

# Controls




Fig. 15

- Carry out action steps according to the illustration.
- WiFi connection and other WiFi settings are reset to factory settings.

## Showing information about the WiFi connection



Fig. 16




Fig. 17

Carry out action steps according to the illustration.

#### 5 ° Temperature

Use this function to set the temperature.

The temperature depends on the following factors:

- Frequency of door opening
- Duration of door opening
- Room temperature of the installation site
- Type, temperature and quantity of food

Temperature zone	Factory-set temperature	Recommended setting
5 ° Fridge section	5 °C	4 °C

#### Setting the temperature




Fig. 18 Example illustration

- ▶ Carry out action steps according to the illustration.
- Temperature is set.




## Temperature unit

Use this function to set the temperature unit. You can set degrees Celsius or degrees Fahrenheit as the temperature unit.

## Setting the temperature unit



Fig. 19



*Fig. 20 Example illustration: Switch from degrees Celsius to degrees Fahrenheit.* 

- Carry out action steps according to the illustration.
- ▶ The temperature unit is set.




You can use this function to activate or deactivate Super-Cool. If SuperCool is activated, then the appliance increases the cooling capacity. It allows you to achieve lower cooling temperatures. You can activate SuperCool when you would like to cool a large quantity of food quickly.

If the function is active, the appliance operates at higher power. As a result, the appliance's operating noise may be temporarily louder and energy consumption will increase.

## Activating SuperCool

Time for activation of the function:

- When you would like to store fresh food in the fridge section: Activate the function when inserting food.



#### Fig. 21



### Fig. 22

- Carry out action steps according to the illustration.
- SuperCool is activated.

### Deactivating SuperCool

SuperCool is deactivated automatically after 18 hours. However, you can also deactivate SuperCool manually at any time:



### Fig. 23



Fig. 24

- Carry out action steps according to the illustration.
- SuperCool is deactivated.
- ▶ The appliance continues to run in normal mode.
- ▶ The appliance cools to the temperature set previously.

# PowerCool

You can use this function to activate or deactivate Power-Cool. PowerCool ensures optimised temperature layers for cooling your food.

The function applies to the fridge section.

### Application:

- At higher room temperatures (as of approx. 35 °C)
- At high humidity, e.g. on summer days
- When storing moist food, in order to prevent condensate forming in the interior

### Note

The fan may also run even if the function is deactivated. It therefore ensures even temperature distribution in the appliance.

If the function is active, the device operates at higher power. As a result, the device's operating noise may be temporarily louder and energy consumption will increase.

### Activating PowerCool





Fig. 25



### Fig. 26

Carry out action steps according to the illustration.
 PowerCool is activated.

### Deactivating PowerCool





Fig. 27



### Fig. 28

- Carry out action steps according to the illustration.
- PowerCool is deactivated.

# PartyMode \*

You can use this function to activate or deactivate Party-Mode. PartyMode activates various functions that are useful for a party.

PartyMode activates the following functions:

- SuperCool (see SuperCool)


You can adjust all listed functions individually and flexibly. When you deactivate PartyMode, all changes are discarded.

If the function is active, the device operates at higher power. As a result, the device's operating noise may be temporarily louder and energy consumption will increase.

### Activating PartyMode







- ► Carry out action steps according to the illustration.
- > PartyMode and the associated functions are activated.
- ▶ The current temperature flashes until the target temperature is reached.

### Deactivating PartyMode

The PartyMode is automatically deactivated after 24 seconds. However, you can also deactivate PartyMode manually at any time:




Fig. 31




Fig. 32

- Carry out action steps according to the illustration.
- PartyMode is deactivated.
- ► The appliance cools to the temperature set previously: The current temperature flashes until the target temperature is reached.

# HolidayMode

You can use this function to activate or deactivate Holiday-Mode. If you activate HolidayMode, the fridge section is set to 15 °C. This saves you energy during longer periods of absence and prevents bad odours and growth of mould.

Appliance status when HolidayMode is acti
---

Fridge section cools to 15 °C.

EasyFresh cools to 15 °C.


PartyMode is deactivated.\*

SuperCool is deactivated.

PowerCool is deactivated.

### Activating HolidayMode

- Empty the fridge section completely.
- Empty EasyFresh completely.



### Fig. 33




Fig. 34

- Carry out action steps according to the illustration.
- HolidayMode is activated.
- Temperature display shows HolidayMode symbol.

### Deactivating HolidayMode








Fig. 36

- Carry out action steps according to the illustration.
- HolidayMode is deactivated.
- > The appliance cools to the temperature set previously.



You can use this function to activate or deactivate SabbathMode. If you activate this function, some electronic functions are switched off. As a result, your device meets the religious requirements for Jewish holidays such as Sabbath and complies with STAR-K Kosher certification.

Device status when SabbathMode is active

The status display shows SabbathMode permanently.

All functions on the display are locked except for the **Deactivate SabbathMode function**.

Active functions remain active.

The display remains bright when you close the door.

The interior lighting is deactivated.

Reminders are not implemented. The set time interval stops.

Reminders and warnings are not displayed.

There is no door alarm.

There is no temperature alarm.

The defrosting cycle operates only for the specified time, without considering the appliance consumption.

After a power failure, the appliance returns to SabbathMode.

Device status

### Note

This appliance has certification from the "Institute for Science and Halacha". (www.machonhalacha.co.il)

You can find a list of STAR-K-certified appliances at www.star-k.org/appliances.

### Activating SabbathMode

# 

Danger of food poisoning from spoiled food!

If you have SabbathMode activated and a power failure occurs, no message appears in the status display about the power failure. Once the power is restored, the appliance continues to operate in SabbathMode. The power failure may mean that food spoils and the consumption of this food could lead to food poisoning.

After a power failure:

Do not consume food that was frozen and has thawed out.




Fig. 37




Fig. 38

- Carry out action steps according to the illustration.
- SabbathMode is activated.
- ▶ The status display shows SabbathMode permanently.

### Deactivating SabbathMode

The SabbathMode is automatically deactivated after 80 hours. However, you can also deactivate SabbathMode manually at any time:




Fig. 39

- Carry out action steps according to the illustration.
- SabbathMode is deactivated.

# E-Saver

You can use this function to activate or deactivate Energy saving mode. If energy saving mode is activated, the energy consumption decreases and the temperature in the device increases. The food remains fresh, but the shelf life is shortened.

Temperature zone	Recommended setting (see Setting the temperature)	Temperature with active E- Saver
5 ° Fridge section	4 °C	7 °C

Temperatures

Activating E-Saver



Fig. 40




Fig. 41

- Carry out action steps according to the illustration.
- Energy saving mode is activated.

### **Deactivating E-Saver**



Fig. 42



Fig. 43

Carry out action steps according to the illustration.
 Energy saving mode is deactivated.

# CleaningMode

You can use this function to activate or deactivate Cleaning-Mode. CleaningMode enables the appliance to be cleaned conveniently.

This setting applies to the fridge section.

Application:


- Clean the fridge section. (see 9.5 Cleaning the appliance)

Device status when CleaningMode is active
The status display shows CleaningMode permanently.
The fridge section is switched off.
Interior lighting is activated.
The reminders and warnings are not displayed. No signal tone sounds.

Device status

### Activating CleaningMode





### Fig. 45

- Carry out action steps according to the illustration.
- CleaningMode is activated.
- > The status display shows CleaningMode permanently.

### Deactivating CleaningMode

CleaningMode is deactivated automatically after 60 minutes. However, you can also deactivate Cleaning-Mode manually at any time:



Fig. 46

- Carry out action steps according to the illustration.
- CleaningMode is deactivated.
- > The appliance cools to the temperature set previously.

# Display brightness

Use this function to set the display brightness in stages.

You can select the following brightness levels:

- 40 %
- 60 %
- 80 %
- 100 % (pre-setting)

### Setting the brightness



 $\Rightarrow \bigotimes_{i} \Rightarrow \bigotimes_{i} \Rightarrow \bigotimes_{i} \Rightarrow \xrightarrow{i} \rightarrow \rightarrow \rightarrow \rightarrow \rightarrow \rightarrow}$ 

Fig. 48 Example illustration: Switch from 80 % to 60 %.
Carry out action steps according to the illustration.
▶ The brightness is set.

# Door alarm


Use this function to activate or deactivate the door alarm. The door alarm sounds if the door is open for too long. The door alarm is activated on delivery. You can set how long the door may be open before the door alarm sounds. The following values can be set:

- 1 minute
- 2 minutes
- 3 minutes
- Off

### Setting the door alarm



Fig. 49




*Fig. 50 Example illustration: Change door alarm from 1 minute to 3 minutes.* 

- Carry out action steps according to the illustration.
- ▶ The door alarm is set.

### Deactivating the door alarm



Fig. 52



### Fig. 53

- Carry out action steps according to the illustration.
- The door alarm is deactivated.



You can use this function to activate or deactivate the input lock. The input lock prevents the appliance being operated accidentally, e.g. by children.

### Application:

- Avoid unintentional modification of functions.
- Avoid unintentional switching off of the device.
- Avoid unintentional temperature setting.

### Activating the input lock

If you activate the input lock, you can continue to navigate in the menus but you cannot select or change other functions.

### Indicating the software version



Fig. 60



Fig. 61

- Carry out action steps according to the illustration.
- Display indicates software version.

# Reminder

Use this function to activate or deactivate the reminders. The function is activated on delivery.

If the function is activated, the following reminders will appear:

- Replace the FreshAir activated carbon filter (see Replace the FreshAir activated carbon filter)

### Activating the reminder



Fig. 62




Fig. 63

Carry out action steps according to the illustration.
 Reminder is activated.

### Deactivating the reminder



#### Fig. 64




Fig. 65

- Carry out action steps according to the illustration.
- Reminder is deactivated.

### Demo mode

Demo mode is a special feature for dealers who want to demonstrate appliance features. If you activate demo mode, all refrigeration functions are deactivated.

If you switch on your appliance and "Demo" appears in the status display, then demo mode is already activated.



Fig. 54



### Fig. 55

Carry out action steps according to the illustration.
 Input lock is activated.

### Deactivating the input lock



### Fig. 56




Fig. 57

- Carry out action steps according to the illustration.
- Input lock is deactivated.

### Device information

Use this function to indicate the model name, index, serial number and service number of your device. You will need the device information when you contact customer service. (see 10.4 Customer Service)

This function also opens the Advanced menu. (see 3 Functionality of the Touch display)

### Indicating the device information



Fig. 58



Fig. 59

- Carry out action steps according to the illustration.
- Display indicates device information.



### Software

Use this function to indicate the software version of your device.

If you activate and then deactivate demo mode, the appliance will be reset to factory defaults. (see Resetting to factory settings)

### Activating demo mode








Fig. 67

- Carry out action steps according to the illustration.
- ▶ Demo mode is activated.
- ▶ Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
- ▶ "DEMO" appears in the status display.

### Deactivating demo mode



Fig. 68





Fig. 69

- Carry out action steps according to the illustration.
- Demo mode is deactivated.
- > Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
- ▶ Appliance is reset to factory settings.



Use this function to reset all settings to factory defaults. All settings you have made so far are reset to their original settings.

### Performing a reset



Fig. 70




Fig. 71

- Carry out action steps according to the illustration.
- Device is reset.
- Device is switched off.
- Restart the device. (see 4.1 Switching on appliance (first use))

### 7.3 Messages

There are two categories of messages:

Category	/ Importance	
Warning	Warnings appear in the event of a door alarm or malfunction.	
	Simple warnings can be cancelled by yourself. In the event of serious malfunctions, you must contact customer service. (see 10.4 Customer Service)	
Reminder	Reminders remind you of general processes. You can carry out these operations to end the message.	

### 7.3.1 Overview of warnings

Behaviour of the appliance in the event of warnings:

- Warning appears on the display.
- The alarm tone sounds at an ever-increasing volume.
- The interior lighting pulsates for some warnings.

Message	Cause	Exit the message
	The message appears if the door is open for too long.	
Door alarm		
	The message appears if there is an appliance error.	

The message appears if there is an appliance error. A component of the appli- ance has a fault.	Carry out action steps (see Error) .

## 7.3.2 Ending warnings

### Door alarm

Error




Fig. 72 Example illustration

- Carry out action steps according to the illustration.
- or-Close the door.
- > The display returns to the status indicator.

You can set how long the door may be open before the door alarm sounds. (see Setting the door alarm)

### Error



- Fig. 73 Example illustration
- Press the confirmation symbol.
- Error code is displayed.
- Note the error code.
- Press the confirmation symbol.

- ▶ The display returns to the status indicator.
- Contact Customer Service. (see 10.4 Customer Service)

### 7.3.3 Overview of reminders

Behaviour of the appliance during reminders:

- Reminder appears on the display.
- Alarm tone sounds.
- The interior lighting pulsates for some reminders.

Message	Cause	Exit the message
FreshAir Replace the Fres- hAir activated carbon filter	appears when the	Carry out action steps (see Replace the FreshAir acti- vated carbon filter) .

### 7.3.4 Ending reminders

### Replace the FreshAir activated carbon filter

Liebherr recommends: Replace the FreshAir activated carbon filter every 6 months.

### Note

FreshAir activated charcoal filters can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/ shop/de/deu/zubehor.html.



Fig. 74 Example illustration

- Press the confirmation symbol.
- Replace the activated carbon filter. (see 9.1 FreshAir carbon filter)
- Activated carbon filter ensures optimum air quality in the cooling unit.
- Reminder appears again after 6 months.

If you no longer wish to receive this reminder, you can deactivate it. (see Deactivating the reminder)

# 8 Features

## 8.1 Door rack

Door racks are suitable for storing drinks and food. You can move door racks for your own individual use and take them apart for cleaning. However, Liebherr recommends using the door racks in the position in the door as delivered from the factory.




Fig. 75 Example illustration, Door rack(1) Shelf




Fig. 76 Example illustration, Door rack with bottle holder(1) Shelf(2) Bottle holder

The following table shows examples of what can be stored in each door rack. Do not exceed the maximum loading weight of the door.

Door rack	Food
Door rack (see Fig. 75)	Butter, cheese, tinned food, tubes
Door rack with bottle holder (see Fig. 76)	Bottles The sliding bottle holder secures the bottles in the door rack.

### 8.1.1 Removing the door rack




Fig. 77 Example illustration

- ▶ Push the door rack upwards.
- ▶ Pull the door rack forward.

### 8.1.2 Inserting the door rack




Fig. 78 Example illustration

- ▶ Slide in the door rack.
- Press the door rack down.

### 8.1.3 Removing the bottle holder




Fig. 79

- ▶ Slide the bottle holder to the side as far as the recess.
- Remove the bottle holder forwards.

### 8.1.4 Inserting the bottle holder




Fig. 80

- Insert the bottle holder in the recess.
- ▶ Push the bottle holder to the desired position to the side.

# 8.2 Shelves

### 8.2.1 Adjusting/removing the shelves

The shelves are prevented from being pulled out accidentally by pull out stops.




Fig. 81

- ► Lift the shelf and pull forward.
- ▶ Line up the side runner.
- Adjust the height of the shelf: Lift or lower it to the desired height and slide it in.

-or-



### Fig. 82

- Remove the shelf completely: Pull it out to the front.
- Easier removal: Set the shelf at an angle.
- ▶ Insert the shelf again: Slide it in all the way.
- ▶ The pull-out stoppers point downwards.
- > The pull-out stoppers are behind the front support.

You can also remove the shelf above the EasyFresh compartments.




Fig. 83

Removing the shelf:

- ▶ Lift the shelf at the front and back.
- Pull it out towards you.

Do not store any goods on the compartment cover below! Inserting the shelf:

- Place the shelf at an angle, sloping down towards the ► back.
- ⊳ The pull-out stoppers point downwards.
- ► Slide the shelf into place.

### 8.2.2 Dismantling the shelves

The shelves can be dismantled for cleaning.




Fig. 84

Dismantling the shelf.

# 8.3 Dividing shelf\*

### 8.3.1 Using the dividing shelf

The shelves are prevented from being pulled out accidentally by pull out stops.




Fig. 85

Push the dividing shelf underneath as shown.




Fig. 86

### Adjusting the height:

- Pull the glass panels out Fig. 86 (1) from the front, one at a time.
- Release the support rails and click in at the height you want.
- Slide in the glass panels one at a time.
- > Flat pull-out stoppers at the front, right behind the support rails.
- ▶ High pull-out stoppers at the back.

### Using both shelves:

- ▶ Hold the glass panel with one hand and pull it to the front
- The glass panel Fig. 86 (1) and trim strip are at the front. ⊳
- ▶ The stops *Fig. 86 (3)* point down.

# 8.4 VarioSafe \*

The VarioSafe offers space in the refrigerator compartment for small groceries, packages, tubes and jars, for example.





Fig. 87

- (1) VarioSafe drawer
- (3) Recesses on the left and
- (2) Side panels with ribs for VarioSafe drawer
- right side panel
- (4) Stop edge
- 8.4.1 Inserting the VarioSafe



Insert the VarioSafe into the fridge section at an angle ► Fig. 88 (1) until the recesses in the side Fig. 88 (2) of the VarioSafe are at the level of the support rib in the fridge section.




Fig. 89

Set VarioSafe straight. Fig. 89 (1)

\* Depending on model and options

▶ Lift VarioSafe at the front. *Fig. 89 (2)* 




Fig. 90

- ► Lift VarioSafe up toward the front.
- ▶ Push VarioSafe in to the rear.
- Lower VarioSafe.
- VarioSafe audibly engages.
- ► VarioSafe is inserted.

### 8.4.2 Repositioning the VarioSafe

You can move the VarioSafe as a whole in the refrigerator compartment.




Fig. 91

► Lift VarioSafe at the front.




Fig. 92

▶ Pull VarioSafe forwards until the recesses in the side of the VarioSafe are at the level of the support rib in the refrigerator compartment. *Fig. 92 (1)*  Move VarioSafe up or down in the refrigerator compartment until the desired height is reached. Fig. 92 (2)




Fig. 93

- ► Lift VarioSafe at the front.
- Push VarioSafe in to the rear.
- ▹ VarioSafe audibly engages.
- VarioSafe is offset in height.

### 8.4.3 Moving the VarioSafe drawer

You can use the VarioSafe drawer at two different heights. If you would like to store taller foodstuffs in the VarioSafe drawer, slide the VarioSafe drawer in on the bottom rib. If you would like to store smaller foodstuffs in the VarioSafe drawer, slide the VarioSafe drawer in on the top rib.





Fig. 94


- ▶ Pull out the VarioSafe drawer as far as it will go.
- ► Lift the VarioSafe drawer up at the front.
- Remove the VarioSafe drawer to the front.



- Lift the VarioSafe drawer up at the front.
- Place the VarioSafe drawer behind the stoppers on desired rib Fig. 95 (1) or Fig. 95 (2).
- VarioSafe drawer is offset in height.

### 8.4.4 Removing the VarioSafe

You can remove the VarioSafe as a whole.





► Lift VarioSafe at the front.




Fig. 97

▶ Pull VarioSafe forwards *Fig. 97 (1)* until the recesses in the side of the VarioSafe are at the level of the support rib in the fridge section. *Fig. 97 (2)* 




Fig. 98

- Set VarioSafe in refrigerator compartment at an angle. Fig. 98 (1)
- ► Take VarioSafe out to the front. *Fig. 98 (2)*
- ► VarioSafe is removed.

## 8.4.5 Disassembling the VarioSafe

You can disassemble the VarioSafe into its individual parts if you want to clean the VarioSafe or if you need to install or remove parts.




Fig. 99

- Remove VarioSafe as a whole. (see 8.4.4 Removing the VarioSafe )
- ▶ Disassemble VarioSafe according to the illustration.

# 8.5 Drawers

You can remove the drawers for cleaning.

The way to remove/insert the drawers varies depending on the pull-out system. Your appliance can contain various pull-out systems.

### Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.

Always leave the fan air vents clear on the back wall!

### 8.5.1 Drawer on appliance base or glass shelf

The drawer runs directly on the appliance base or on a glass shelf. There are no rails.

When you remove the drawers, you can use the glass shelves below them as storage shelves.\*

### **Removing drawer**




Fig. 100

▶ Remove drawer as shown in the illustration.

### Inserting drawer




Fig. 101

▶ Insert drawer as shown in the illustration.

### 8.5.2 Drawer on rails

### **Removing drawer**




Fig. 102

• Remove drawer as shown in the illustration.

### Inserting drawer




Fig. 103

▶ Insert drawer as shown in the illustration.

### 8.5.3 Drawer on telescopic rails

The drawer runs on extendible rails (telescopic rails). There are fully extendible telescopic rails and telescopic rails with partial pull-out. Drawers which are fully extendible can be pulled out fully from the appliance. Drawers with partial pull-out cannot be removed fully from the appliance. The system in your appliance depends on the type of appliance.

### Partial pull-out fridge compartment

### **Removing drawer**




Fig. 104

- Pull out drawer half-way. Fig. 104 (1)
- Push the drawer down at the front. Fig. 104 (2)
- Push the left rail in by about 2 cm. Fig. 104 (3)
- Push the right rail in by about 2 cm. Fig. 104 (4)
- Remove drawer to the front. Fig. 104 (5)





Fig. 105

If the rails are not yet fully inserted after removing the drawer:

▶ Push rails in completely.

### Inserting drawer



Slide rails in.

- Place drawer on rails.
- Slide in drawer to the back.

## 8.6 Compartment lid for EasyFresh Safe

The compartment lid ensures constant levels of humidity. The compartment lid is directly on the drawer and can be covered by shelves or additional drawers.





Fig. 107 Example illustration, compartment lid for EasyFresh Safe

(3) Shelf


- (1) EasyFresh Safe
- (2) Compartment lid for
  - EasyFresh Safe

### 8.6.1 Reducing the air humidity in the drawer



- Pull out the drawer Fig. 108 (1).
- ▶ Grasp the recessed grip *Fig. 108 (2)* on the compartment lid and pull the compartment lid forwards at the same time.
- ▶ When the drawer is closed, there is a small gap between the compartment lid and the drawer.

### 8.6.2 Increasing the air humidity in the drawer



### Fig. 109

- ▶ Pull out the drawer *Fig. 109 (1)*.
- ▶ Grasp the recessed grip *Fig. 109 (2)* on the compartment lid and push the compartment lid backwards at the same time.
- ▶ When the drawer is closed, the compartment lid seals with the drawer.

# 8.7 Pull-out board with bottle basket\*

Removable bottle baskets on the pull-out board offer plenty of space to store bottles. You can remove the bottle baskets to make room for a drinks crate in the pull-out board.

### 8.7.1 Using the bottle basket




Fig. 110

- Slide the bottle rack at the edges.
- > The bottles are prevented from falling over.

### 8.7.2 Disassembling the pull-out board

The pull-out board is mounted on a glass panel with pull-out rails.

You can dismantle the pull-out board for cleaning.

### Removing the pull-out board

Remove the bottle baskets.




Fig. 111

• To remove the pull-out board with glass panel: Gently lift the glass panel at the front *Fig. 111 (1)* and pull out to the front *Fig. 111 (2)*.





Fig. 112

- Slide the pull-out board all the way in Fig. 112 (1).
- Release the clips at the back Fig. 112 (2).
- Remove the pull-out board from the front Fig. 112 (3).

### Inserting the pull-out board



### Fig. 113

- Place centrally on the rails Fig. 113 (1).
- Slide the pull-out board all the way in Fig. 113 (2).
- Press down at the back until it clicks into place Fig. 113 (3).
- ► To insert the pull-out board with glass panel: Slide to the rear.

## 8.8 Glass shelves\*

You can remove the glass shelves under the drawers for cleaning.

### 8.8.1 Removing / inserting the glass shelf

Make sure that the following requirements are fulfilled:

Pull-out board under the bottle basket: Bottle basket has been removed. (see 8.7 Pull-out board with bottle basket\*) \*

# Maintenance

### Removing glass shelf




Fig. 114 Example illustration, glass shelf
Lift the glass shelf forwards.
Remove the glass shelf forwards.

### Inserting glass shelf




Fig. 115 Example illustration, glass shelf

- ▶ Place the glass shelf at an angle behind the stoppers.
- Lower glass shelf.
- Slide in glass shelf to the back.

### 8.9 Bottle holder

### 8.9.1 Using the bottle holder





Fig. 116

- Push the bottle holder onto the bottles.
- ▶ The bottles are prevented from falling over.

# 8.10 FlexCube\*

The FlexCube has different sized openings, so you can store small items such as tubes, open yoghurt pots or quail eggs in it. The FlexCube fits into all Liebherr door racks, for example. If necessary, you can also set up several Flex-Cubes next to each other.



### Fig. 117 Example illustration

#### Note

These accessories can be purchased from the Liebherr-Hausgeräte shop at home.liebherr.com/shop/de/deu/zubehor.html.

### 8.10.1 Using the FlexCube




Fig. 118 Example illustration

▶ Insert the FlexCube in the door rack.

#### -or-




Fig. 119 Example illustration

- Place FlexCube on shelf.
- Sort small parts into the FlexCube for storage.

# 9 Maintenance

### 9.1 FreshAir carbon filter

The FreshAir carbon filter is in the compartment above the fan.

It guarantees the best air quality.

- **□** Replace the carbon filter every 6 months.
- When the reminder is set, a message on the display prompts you to change it.
- The carbon filter can be disposed of with the regular household waste.

### Note

FreshAir activated charcoal filters can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/zubehor.html.

### 9.1.1 Removing the FreshAir carbon filter




Fig. 120

- ▶ Pull out the compartment *Fig. 120 (1)*.
- Remove the carbon filter *Fig. 120 (2)*.

### 9.1.2 Inserting the FreshAir carbon filter




Fig. 121

- ▶ Insert the carbon filter as shown in the diagram *Fig. 121 (1)*.
- ▶ The carbon filter clicks into place.
- If the carbon filter is pointing downwards:
- Push the compartment in Fig. 121 (2).
- ▶ The carbon filter is now ready for use.

# 9.2 Disassembling / assembling pullout systems

### 9.2.1 Notes on disassembly

You can disassemble some of the pull-out systems for cleaning. Your appliance can contain a variety of pull-out systems.

The following pull-out systems can be disassembled or cannot be disassembled:

Pull-out system	can be disassembled / cannot be disassembled
Drawer on appliance base or glass shelf	cannot be disassembled
Drawer on rails	cannot be disassembled
Fridge section partial pull-out	cannot be disassembled

Pull-out system		can be disassembled / cannot be disassembled
Pull-out shelf bottle basket*	with	can be disassembled (see 9.2.2 Pull-out board with bottle basket*) *

# 9.2.2 Pull-out board with bottle basket\*

### Disassembling pull-out system

Make sure the following prerequisites are met:

- Bottle basket has been removed. (see 8.7 Pull-out board with bottle basket\*)
- $\hfill\square$  Glass shelf has been removed. (see 8.8 Glass shelves\*)




Fig. 122 Glass shelf with rails

- ▶ Push up front click-in hooks. Fig. 122 (1)
- ▶ Move the pull-out rails to the side *Fig. 122 (2)* and to the rear *Fig. 122 (3)*.

### Installing pull-out system




Fig. 123 Glass shelf with rails

- Hook in rail at the back. Fig. 123 (1)
- Hook in rail at the front. Fig. 123 (2)

# 9.3 Compartment lid for EasyFresh Safe

You can remove the compartment lid for cleaning.

### 9.3.1 Removing the compartment lid

Ensure that the following requirements are met:

- □ The shelf directly above the drawer has been removed. (see 8.2 Shelves)
- □ The drawer directly below the compartment lid has been removed. (see 8.5 Drawers)




Fig. 124

- Push the compartment lid backwards.
- ▶ Lift the compartment lid forwards.

# Maintenance

Remove the compartment lid forwards and upwards at an angle.

### 9.3.2 Inserting the compartment lid




Fig. 125

If the THIS SIDE UP lettering is at the top:

- Insert the rear retaining parts into the relevant rear openings.
- Push the compartment lid backwards.
- Lower the compartment lid forwards and engage the front retaining parts into the openings.
- ▶ Move the compartment lid into the required position.

# 9.4 Defrosting the appliance

# 

Improper defrosting of the appliance! Injuries and damage.

- Do not use mechanical equipment or other methods to speed up the defrosting process other than those recommended by the manufacturer.
- Do not use electrical heating or steam-cleaning appliances, naked flames or defroster sprays to defrost.
- Do not use sharp objects to remove ice.

Defrosting is performed automatically. The water from the thawing process drains through the outlet and evaporates.

Water drops or a thin layer of frost or ice can form on the back wall; this is a completely normal part of the appliance's function. This must not be removed.

A layer of frost or ice can from briefly due to the energyoptimised control of the device.

 Clean the drain opening at regular intervals. (see 9.5 Cleaning the appliance)

# 9.5 Cleaning the appliance

### 9.5.1 Ready



Danger of electric shock!

Remove the refrigerator connector or interrupt the power supply.

# 

Risk of fire

Do not damage the refrigeration circuit.

Empty the appliance.

Remove mains connector.or-

► Activate CleaningMode. (see CleaningMode)

### 9.5.2 Clean the housing

### NOTICE

Improper cleaning!

- Damage to the appliance.
- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

# 

Risk of injury and damage as a result of hot steam! Hot steam can lead to burns and can damage the surfaces.

- Do not use any steam cleaners!
- ▶ Wipe the housing down with soft, clean cloth. If very dirty, use lukewarm water with a neutral cleaner. Glass surfaces can also be cleaned with glass cleaner.

### 9.5.3 Cleaning the interior

### NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.
- Plastic surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Metal surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Drain hole: remove deposits using a thin item (for example a cotton bud).

### 9.5.4 Clean the components

### NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

# Clean with a soft, clean cloth, lukewarm water and some detergent:

- Door rack
- Shelf
- Dividing shelf\*
- VarioSafe\*
- Bottle basket and pull-out panel\*
- Compartment lid for EasyFresh Safe
- Drawer

### Clean with a damp cloth:

 Retractable rails Please note: The grease in the tracks is used for lubrication and must not be removed!

### Wash in the dishwasher up to 60 °C:

Bottle rack

- Holder of the dividing shelf\*
- FlexCube\*
- ► To disassemble components: see the relevant section.
- Clean the components.

## 9.5.5 After cleaning

- Wipe the appliance and the components dry.
- Connect and switch on the appliance. The temperature is cold enough:
- Place the food inside.
- Repeat cleaning regularly.

# 10 Customer help

# 10.1 Technical specifications

Temperature range	
Cooling	2 °C to 9 °C

Maximum loading weight for the equipment
haxing weight for the equipment

haxing weight for the equipment			
Equipment	Appliance width 600 mm (see installa- tion instruc- tions, device dimen- sions)	Appliance width 700 mm (see instal- lation instruc- tions, device dimen- sions)	Appliance width 750 mm (see installa- tion instruc- tions, device dimen- sions)
Pull-out shelf*	20 kg*	20 kg*	*

Lighting	
Class <sup>1</sup>	Light source
This product contains one or more energy LED efficiency class G light sources.	

<sup>1</sup> The appliance may contain light sources with different energy efficiency classes. The lowest energy efficiency class is indicated.

# 10.2 Operating noises

The appliance makes different noises when it is on.

- At higher temperatures the appliance uses less energy but works for longer. It is quieter.
- At lower temperatures the food is cooled faster. It is louder.

Examples:

- Functions on (see 7.2 Appliance functions)
- Fan running
- Food recently added

- High ambient temperature
- Door open for a while

Noise		Possible cause		Туре	Type of noise	
Bubbling splashing	and	Coolant into the circuit.	flowing cooling	Nori nois		
Hissing		Coolant into the circuit.	sprays cooling	Nori nois		
Humming		The is cooli volume on the output.	appliance ng. The depends cooling	Nori nois		
Suction noises	3	Soft-closi is being and close	opened	Nori nois		
Humming rustling			running.	Nori nois		
Clicking	Compone switched off.		nts are on and	Nori nois		
Rattling humming	or	Valves or working.	flaps are	Nori nois		
Noise	Pos: cau	sible se	Type of no	oise	Lifting	
Vibration	Improper setup		Defective noise		Level the appliance using the adjustable feet.	
Rattling	item	nponents, ns inside appliance	Defective noise		Secure components. Leave enough space between the items.	

# 10.3 Technical fault

Your appliance is designed and built to ensure it works reliably and has a long service life. In the unlikely event that a fault occurs during operation, please check whether it is due to an operating error. If so, you will be charged for the callout and repair costs even if it falls within the warranty period.

You can fix the following faults yourself.

## 10.3.1 Appliance function

Defect	Cause	Remedy
The appliance is	$\rightarrow$ The appliance is not switched on.	<ul> <li>Switch the appliance on.</li> </ul>
not working.	→ The power plug is not properly plugged into the socket.	<ul> <li>Check the power plug.</li> </ul>
	→ There is something wrong with the power outlet fuse.	<ul> <li>Check the fuse.</li> </ul>

Defect	Cause	Remedy
	→ Power cut	► Keep the appliance closed.
	→ The IEC socket is not plugged into the appliance correctly.	<ul> <li>Check the IEC socket.</li> </ul>
Temperature is not cold enough.	→ The appliance door is not closed properly.	<ul> <li>Close the appliance door.</li> </ul>
	→ The ambient temperature is too high.	Problem solution: (see 1.4 Appliance range of use)
	→ The appliance was opened too many times or for too long.	<ul> <li>Wait to see if the required temperature corrects itself. If not, contact Customer Service. (see 10.4 Customer Service)</li> </ul>
	ightarrow The temperature is set incorrectly.	► Turn down the temperature and check after 24 hours.
	→ The appliance is too close to a heat source (oven, radiator, etc).	Move the appliance or the heat source.
The door seal is defective or needs to be replaced for another reason.	→ The door seal can be replaced. It can be replaced without the need for special tools.	<ul> <li>Contact Customer Service. (see 10.4 Customer Service)</li> </ul>
The appliance builds up too much ice or condensa- tion.	→ The door seal may have slipped out of its groove.	<ul> <li>Check that the door seal is well fitted in the groove.</li> </ul>
The exterior surfaces of the appliance are warm.*	→ The heat of the refrigeration circuit is used to avoid condensation.	<ul> <li>This is normal.</li> </ul>

### 10.3.2 Features

Defect	Cause	Remedy
The internal light	$\rightarrow$ The appliance is not switched on.	<ul> <li>Switch the appliance on.</li> </ul>
does not come on.	→ The door was open for longer than 15 minutes.	Interior lighting switches off automatically after about 15 minutes when the door is open.
	→ The LED interior light is faulty or the lid is damaged.	<ul> <li>Contact Customer Service. (see 10.4 Customer Service)</li> </ul>

# **10.4 Customer Service**

First check whether you can rectify the fault yourself (see 10 Customer help) . If you cannot rectify the problem, contact Customer Service.

You can find the address in the enclosed brochure "Liebherr-Service" or at home.liebherr.com/service.



### Unprofessional repair!

Injuries.

- Have any repairs and action not expressly specified on the appliance and mains cable carried out by service personnel only. (see 9 Maintenance)
- ► A damaged mains cable may only be replaced by the manufacturer, the manufacturer's Customer Service or a similarly qualified person.
- ▶ In the case of appliances with an IEC connector, the change may be made by the customer.

### 10.4.1 Contacting Customer Service

Make sure that the following appliance information is available:

- □ Appliance name (model and index)
- Service no. (Service)
- Serial no. (S no.)
- Call up the appliance information via the display. (see Device information)

-or-

- Refer to the type plate for appliance information. (see 10.5 Model plate)
- ▶ Note down the appliance information.
- Notify customer service: Report errors and the appliance information.
- ▶ This will help us to provide you with a faster, more accurate service.
- ► Follow further instructions from Customer Service.

# 10.5 Model plate

The model plate is behind the drawers on the inside of the appliance.




Fig. 126

- (1) Appliance description (3) Serial no. (2) Service no.
- Note the data on the model plate.

# 11 Shutting down

- Empty the appliance.
- Switch off appliance. (see Switching the appliance off ► and on)
- Pull the mains plug out of the socket.
- Remove the IEC socket if required: Pull the IEC socket out of the appliance plug and move it to the left and right at the same time.
- Clean appliance. (see 9.5 Cleaning the appliance)
- ▶ Leave the door open, so that no unpleasant odours arise.

# 12 Disposal

# 12.1 Preparing appliance for disposal



Liebherr uses batteries in some of its appliances. In the EU, for environmental reasons, legislation obliges the end user to remove these batteries before disposing of old appliances. If your appliance contains batteries, a corresponding notice is attached.

Lamps

- If you can remove the lamps yourself without destroying them, also remove these before disposal.
- Take the appliance out of operation.
- ▶ If possible: remove lamps without destroying them.

### 12.2 Disposing of the appliance in an environmentally friendly manner



The appliance still contains valuable materials and must be disposed of separately from unsorted municipal waste.



Dispose of batteries separately from the old appliance. To do this, you can return the batteries free of charge to retailers as well as recycling centres and collection centres for recyclable materials.

Lamps

Dispose of removed lamps via the respective collection systems.

Shutting down

For Germany:

You can dispose of the appliance free of charge via the class 1 collection containers at the local recycling and recyclable material collection centres. When purchasing a new fridge/freezer, if the sales area > 400 m<sup>2</sup>, retailers will also take back the old appliance free of charge.



Leaking coolant and oil!

Fire. The coolant contained in the appliance is eco-friendly, but also flammable. The oil contained in the appliance is flammable. Escaping coolant and oil can ignite if the concentration is high enough and in contact with an external heat source.

- Do not damage the pipelines of the coolant circuit and ► the compressor.
- Observe the notes on transporting the appliance.
- ► Transport the appliance without damaging it.
- Dispose of batteries, lamps and the appliance according to the above specifications.



home.liebherr.com/fridge-manuals



Issue date: 20250507

Part number index: 7083572-00

Liebherr-Hausgeräte Marica EOOD Bezirk Plovdiv 4202 Radinovo Bulgarien